

**Den Braven****Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 31.03.2016


Version number 3

Revision: 31.03.2016

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Application of the substance / the mixture** Sealant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
DEN BRAVEN  
Denariusstraat 11  
4903 RC Oosterhout  
The Netherlands  
Tel: +31 (0)162-491000  
Fax: +31 (0)162-421217  
E-mail: info@denbraven.com  
Internet: www.denbraven.com
- **Further information obtainable from:**  
Product safety department.  
info@denbraven.com
- **1.4 Emergency telephone number:**  
info@denbraven.com  
Tel.: +31 (0)162-491000

**SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**  
 GHS07  
Skin Sens. 1      H317 May cause an allergic skin reaction.  
Aquatic Chronic 3   H412 Harmful to aquatic life with long lasting effects.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**  
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labelling:**  
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate  
N-(3-(trimethoxysilyl)propyl)ethylenediamine  
N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine  
dioctyltinbis(acetylacetonate)
- **Hazard statements**  
H317 May cause an allergic skin reaction.  
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**  
P101      If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 1)

- P102 Keep out of reach of children.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 P273 Avoid release to the environment.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 2768-02-7 EINECS: 220-449-8 Reg.nr.: 01-2119513215-52-xxxx	trimethoxyvinylsilane ----- ☠ Flam. Liq. 3, H226; ☠ Acute Tox. 4, H332	1-<5%
CAS: 54068-28-9 ELINCS: 483-270-6 Reg.nr.: 01-0000020199-67-xxxx	dioctyltinbis(acetylacetonate) ----- ☠ STOT SE 2, H371; ☠ Skin Sens. 1, H317	<1,0%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39-xxxx	N-(3-(trimethoxysilyl)propyl)ethylenediamine ----- ☠ Eye Dam. 1, H318; ☠ Aquatic Chronic 2, H411; ☠ Acute Tox. 4, H332; ☠ Skin Sens. 1, H317	<1,0%
EC number: 915-687-0 Reg.nr.: 01-2119491304-40-xxxx	Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ----- ☠ Aquatic Acute 1, H400; ☠ Aquatic Chronic 1, H410; ☠ Skin Sens. 1A, H317	<1,0%
CAS: 3069-29-2 EINECS: 221-336-6 Reg.nr.: 01-2119963926-21-xxxx	N-[3-(dimethoxymethylsilyl)propyl]ethylenediamine ----- ☠ Eye Dam. 1, H318; ☠ Skin Sens. 1, H317	<1,0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

### SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

GB

(Contd. on page 3)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 2)

### SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation
- **6.2 Environmental precautions:**
  - Do not allow product to reach sewage system or any water course.
  - Inform respective authorities in case of seepage into water course or sewage system.
  - Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
  - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
  - Dispose contaminated material as waste according to item 13.
  - Pick up mechanically.
  - Ensure adequate ventilation.
- **6.4 Reference to other sections**
  - See Section 7 for information on safe handling.
  - See Section 8 for information on personal protection equipment.
  - See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
  - Ensure good ventilation/exhaustion at the workplace.
  - Prevent formation of aerosols.
  - Use only in well ventilated areas.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**
- **Ingredients with limit values that require monitoring at the workplace:**
  - The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
  - Immediately remove all soiled and contaminated clothing
  - Wash hands before breaks and at the end of work.

(Contd. on page 4)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 3)

**· Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**· Protection of hands:**


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

**· Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**· Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**· Eye protection:** Goggles recommended during refilling

### SECTION 9: Physical and chemical properties

**· 9.1 Information on basic physical and chemical properties**
**· General Information**
**· Appearance:**

<b>Form:</b>	Pasty
<b>Colour:</b>	Various colours
<b>· Odour:</b>	Characteristic
<b>· Odour threshold:</b>	Not determined.

**· pH-value:** Undetermined.

**· Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	270 °C

**· Flash point:** > 100 °C

**· Flammability (solid, gaseous):** Not applicable.

**· Ignition temperature:** Undetermined.

**· Decomposition temperature:** Not determined.

**· Self-igniting:** Product is not selfigniting.

**· Danger of explosion:** Product does not present an explosion hazard.

**· Explosion limits:**

<b>Lower:</b>	Undetermined.
<b>Upper:</b>	Undetermined.

**· Vapour pressure:** Undetermined.

<b>· Density at 20 °C:</b>	1,48 g/cm <sup>3</sup>
<b>· Relative density</b>	Not determined.
<b>· Vapour density</b>	Not determined.
<b>· Evaporation rate</b>	Not determined.

(Contd. on page 5)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 4)

- |   |  |
|---|--|
| <b>· Solubility in / Miscibility with water:</b>  | Not miscible or difficult to mix.          |
| <b>· Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| <b>· Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| <b>· Solvent content:</b>                         |  |
| <b>VOC (EC)</b>                                   | 1.92 %                                     |
| <b>VOC (EC)</b>                                   | 28.4 g/l                                   |
| <b>· 9.2 Other information</b>                    | No further relevant information available. |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation**  
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

### SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.  
Harmful to aquatic organisms

(Contd. on page 6)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 5)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- **European waste catalogue**

08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances
-----------	--

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |  |                 |
|--|-----------------|
| · <b>14.1 UN-Number</b>  | Void            |
| · <b>ADR, ADN, IMDG, IATA</b>  | Void            |
| · <b>14.2 UN proper shipping name</b>  | Void            |
| · <b>ADR, ADN, IMDG, IATA</b>  | Void            |
| · <b>14.3 Transport hazard class(es)</b>   | Void            |
| · <b>ADR, ADN, IMDG, IATA</b>  | Void            |
| · <b>Class</b>   | Void            |
| · <b>14.4 Packing group</b>  | Void            |
| · <b>ADR, IMDG, IATA</b>   | Void            |
| · <b>14.5 Environmental hazards:</b>   | Not applicable. |
| · <b>14.6 Special precautions for user</b>                                       | Not applicable. |
| · <b>14.7 Transport in bulk according to Annex II of Marpol and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>  | Void            |

### SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**  
H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H332 Harmful if inhaled.

(Contd. on page 7)

# Safety data sheet

## according to 1907/2006/EC, Article 31

Printing date 31.03.2016

Version number 3

Revision: 31.03.2016

**Trade name: ZWALUW FIREPROTECT FP HYBRID SEALANT**

(Contd. of page 6)

H371 May cause damage to organs.  
 H400 Very toxic to aquatic life.  
 H410 Very toxic to aquatic life with long lasting effects.  
 H411 Toxic to aquatic life with long lasting effects.

· **Department issuing MSDS:** Product safety department.

· **Contact:** Pascal Timmermans / Kees van Bommel

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Skin Sens. 1A: Sensitisation - Skin, Hazard Category 1A

STOT SE 2: Specific target organ toxicity - Single exposure, Hazard Category 2

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

GB