Acryl Clear WT

How to order

Acryl Clear WT is available in 310 ml cartridges packed per 12 in a box. To order your specific Acryl Clear WT, please find below the article and EAN codes:

Colour:	Article code:	EAN code:
Translucent	11396202	8711595084895



denbraven.com

BETTER RESULTS THROUGH KNOWLEDGE



Acryl Clear WT

Product Descriptions

Acryl Clear WT is a high quality plasto-elastic sealant based on an acrylic dispersion. After application the product forms a translucent tough rubber by evaporation of water from the sealant.

Applications

Acryl Clear WT has been especially developed for sealing connection joints between stairs, walls, ceilings, skirting boards and windowsills for interior applications. Acryl Clear WT can be painted with water and solvent based paints.

Acryl Clear WT

Certifications

EN 15651-1: F-INT

Technical Performances

Density 1,06 g/ml
Shore-A hardness 42°
Elongation at break 540%
Tensile strength 0,70 Mpa
Skin formation 30 minutes

Visit our website to download the full technical specifications of the Acryl Clear WT.









Visit Den Braven YouTube channel

Den Braven offers a wide variety of USP, Application and Commercial movies via here website and YouTube channel. Scan the below displayed QR Code to visit the product page of the original Acryl Clear WT:



denbraven.com