

Foliefix® Spur

How to order

Foliefix® Spur is available in 310 ml cartridges packed per 12 in a box. To order your specific Foliefix® Spur, please find below the article and EAN codes:

Colour:	Article code:	EAN code:
Green	10866901	8711595085236
Black	11460402	8711595143967



Centre of Excellence

Better results through Knowledge

Den Braven 's company payoff is "Better results through Knowledge". Our Centre of Excellence accumulates knowledge which provides her with the latest market insights, developments and trends. This knowledge is shared within the Den Braven Group and amongst our customers and end-users.

This process enables our relations to achieve higher efficiency and better results. This is the true meaning of "Better results through Knowledge". Visit our website to discover more about what the Centre of Excellence could mean for you!



Foliefix® Spur

Hybrid based adhesive for bonding plastic foils and vapour barriers

denbraven.com

BETTER RESULTS THROUGH KNOWLEDGE

Foliefix® Spur

Hybrid based adhesive
for bonding plastic foils
and vapour barriers



- Instant grab
- For plastic building membranes, aluminium, EPDM, paper foils and Kraft paper
- Perfect bonding on stone, concrete, wood and metal
- Flexible adhesion
- Isocyanate and silicone free
- Part of Air Tight Solutions & Passive House portfolio of Den Braven



Foliefix® Spur

Product Descriptions

Foliefix® Spur is a hybrid based adhesive for bonding plastic foils and vapour barriers in the building industry. The product is free of isocyanates, silicones and solvents. After application the adhesive cures with atmospheric moisture to form a durable pressure sensitive rubber mass. Foliefix® Spur stays sticky.

Applications

Foliefix® Spur is designed for the adhesion of plastic foils like PE, PBC, EPDM, DPC, aluminium foil, carton, Kraft paper and non-woven to stone, concrete, plaster, metal and wood. Foliefix® Spur reaches its optimal adhesion after 2 till 3 days at room temperature.



Foliefix® Spur

Technical Performances

Density	1,09 g/ml
Curing time	7 days
Peel strength	6 N/cm
Application temperature	+5° till +50°
Temperature resistance	-40° till +80°

Visit our website to download the full technical specifications of the Foliefix® Spur.



Visit Den Braven YouTube channel

Den Braven offers a wide variety of USP, Application and Commercial movies via here website and YouTube channel. Scan the below displayed QR Code to visit the product page of the original Foliefix® Spur:

