

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

SILICONE OXIM QO16.100A (WHITE) Supercedes Date: 14-Mar-2022

Revision date	0	3-Aug-202	22
Revisio	n	Number	3

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	SILICONE OXIM QO16.100A (WHITE)
Pure substance/mixture	Mixture
1.2. Relevant identified uses of the	substance or mixture and uses advised against
Recommended use	Sealant
Uses advised against	Consumer use.
Reason why uses advised against	Restricted substance per REACH Annex XVII
1.3. Details of the supplier of the sa	afety data sheet
Company Name Bostik Benelux B.V. Denariusstraat 11 4903 RC Oosterhout The Netherlands Tel: + 31 162 491 000	
E-mail address	SDS.box-EU@bostik.com
1.4. Emergency telephone number	_
Emergency Telephone	112
SECTION 2: Hazards identified	cation

#### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin sensitisation	Category 1A - (H317)
Carcinogenicity	Category 1B - (H350)
Chronic aquatic toxicity	Category 3 - (H412)

#### 2.2. Label elements

Contains 2-Butanone, oxime & 2-octyl-2H-isothiazol-3-one [OIT] & 3-aminopropyltriethoxysilane



Signal word

SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

Revision date 03-Aug-2022 Revision Number 3

Danger

#### Hazard statements

H317 - May cause an allergic skin reaction H350 - May cause cancer H412 - Harmful to aquatic life with long lasting effects

#### Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P308 + P313 - IF exposed or concerned: Get medical advice/attention
P362 + P364 - Take off contaminated clothing and wash it before reuse
P501 - Dispose of contents/ container to an approved waste disposal plant

#### Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

#### 2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

#### PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

#### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No.	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Silica, amorphous 1 - <5 %	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499- 16-XXXX
Titanium dioxide 0.1- <1 %	236-675-5	13463-67-7	[C]	-	-	-	01-2119489379- 17-XXXX
2-Butanone, oxime 0.1- <1 %	202-496-6	96-29-7	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)	_	-	-	01-2119539477- 28-XXXX
3-aminopropyltriethoxysil ane 0.1- <1 %	213-048-4	919-30-2	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)	-	-	-	01-2119480479- 24-XXXX
Octamethylcyclotetrasilo xane [D4]	209-136-7	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410)	-	-	10	01-2119529238- 36-XXXX

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

0.01 - <0.1 %			Flam. Liq. 3 (H226)				
			[G]				
2-octyl-2H-isothiazol-3-o	247-761-7	26530-20-1	Acute Tox. 3 (H301)	Skin Sens. 1A ::	100	100	-
ne [OIT]			Acute Tox. 3 (H311)	C>=0.0015%			
0.0015 - <0.01 %			Acute Tox. 2 (H330)				
			Skin Corr. 1B (H314)				
			Eye Dam 1 (H318)				
			Skin Sens. 1A (H317)				
			Aquatic Acute 1 (H400)				
			Aquatic Chronic 1 (H410)				

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Ethanol 64-17-5	200-578-6	1 - <2.5	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	-	-	-	01-211945761 0-43-XXXX
Methyl alcohol 67-56-1	200-659-6	1 - <2.5	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 3 (H331) STOT SE 1 (H370) Flam. Liq. 2 (H225)	STOT SE 1 :: C>=10% STOT SE 2 :: 3%<=C<10%	-	-	01-211939240 9-28-XXXX
2-Butanone, oxime 96-29-7	202-496-6	1 - <2.5	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)	-	-	-	01-211953947 7-28-XXXX

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes

[B] - Substance with a Community workplace exposure limit

[C] - Components with occupational exposure limits and/or biological occupational exposure limits requiring monitoring

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
Titanium dioxide	236-675-5	13463-67-7	-	-	-	-	-
2-Butanone, oxime	202-496-6	96-29-7	100+	1100+	-	-	-
3-aminopropyltriethoxy silane	213-048-4	919-30-2	1490	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7	556-67-2	-	-	-	-	-
2-octyl-2H-isothiazol-3- one [OIT]	247-761-7	26530-20-1	125+	311+	0.27+	0.27 +	0.27+

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No.

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

1907/2006 (REACH), Article 59)

#### Notes

See section 16 for more information

Chemical name	Notes
Titanium dioxide - 13463-67-7	V,W,10

#### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.			
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.			
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.			
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.			
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.			
4.2. Most important symptoms and	d effects, both acute and delayed			
Symptoms	None known.			
4.3. Indication of any immediate m	edical attention and special treatment needed			
Note to doctors	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when the product is exposed to moisture or water. Treat symptomatically.			
SECTION 5: Firefighting me	asures			
SECTION 5: Firefighting me	asures			
	asures Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.			
5.1. Extinguishing media				
5.1. Extinguishing media Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet.			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet.			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <b>he substance or mixture</b>			
5.1. Extinguishing media Suitable Extinguishing Media Unsuitable extinguishing media 5.2. Special hazards arising from the Specific hazards arising from the chemical	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Full water jet. <u>he substance or mixture</u> Thermal decomposition can lead to release of irritating gases and vapours. Carbon oxides. Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead			

#### **SECTION 6: Accidental release measures**

6.1. Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
Other information	Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
6.3. Methods and material for cont	ainment and cleaning up
Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage
7.1. Precautions for safe handling	_
7.1. Precautions for safe handling Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.
-	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product.
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u>	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage temperature	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage temperature <u>7.3. Specific end use(s)</u> Specific use(s) Sealant.	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage temperature <u>7.3. Specific end use(s)</u> Specific use(s) Sealant.	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse. <b>Including any incompatibilities</b> Protect from moisture. Keep away from food, drink and animal feedingstuffs. Keep at temperatures between 10 and 35 °C.
Advice on safe handling General hygiene considerations 7.2. Conditions for safe storage, in Storage Conditions Recommended storage temperature 7.3. Specific end use(s) Specific use(s) Sealant. Risk Management Methods (RMM)	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse. <b>Including any incompatibilities</b> Protect from moisture. Keep away from food, drink and animal feedingstuffs. Keep at temperatures between 10 and 35 °C. The information required is contained in this Safety Data Sheet. Observe technical data sheet.

### 8.1. Control parameters

**Exposure Limits** 

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of

#### titanium dioxide is unlikely to occur from exposure to this product

### Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m <sup>3</sup>
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *

Derived No Effect Level (DNEL)

No information available

Derived No Effect Level (DNEL)					
Titanium dioxide (13463-67-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Local health effects	Inhalation	10 mg/m³			

2-Butanone, oxime (96-29-7)	1		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
DNEL/DMEL	Inhalation	0.028 mg/m <sup>3</sup>	
Long term Systemic health effects			
Long term Local health effects	Inhalation	0.9 mg/m³	
DNEL/DMEL	Dermal	0.004 mg/kg bw/d	
Long term			
Systemic health effects			

3-aminopropyltriethoxysilane (919-30-2)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m³	
worker Short term Systemic health effects	Inhalation	59 mg/m³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Туре	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	-
worker	Inhalation	73 mg/m <sup>3</sup>	
Long term			
Systemic health effects			

Derived No Effect Level (DNEL)			
Titanium dioxide (13463-67-7)			
Туре	Exposure route	Derived No Effect Level	Safety factor

## SILICONE OXIM QO16.100A (WHITE) Supercedes Date: 14-Mar-2022

		(DNEL)	
Consumer	Oral	700 mg/kg bw/d	
Long term			
Systemic health effects			
2-Butanone, oxime (96-29-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term	Inhalation	0.00482 mg/m <sup>3</sup>	
Systemic health effects			
Long term	Dermal	0.43 mg/m <sup>3</sup>	
Local health effects			
3-aminopropyltriethoxysilan	e (919-30-2)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	17 mg/m <sup>3</sup>	
Long term			
Systemic health effects			
Consumer	Inhalation	17.4 mg/m <sup>3</sup>	
Short term			
Systemic health effects			
Consumer	Dermal	5 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Dermal	5 mg/kg bw/d	
Short term			
Systemic health effects			

Octamethylcyclotetrasiloxane [D4	4] (556-67-2)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	13 mg/m³	
Consumer Long term Systemic health effects	Oral	3.7 mg/kg bw/d	

#### Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)	
Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

3-aminopropyltriethoxysilane (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

Octamethylcyclotetrasiloxane [D4] (556-67-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

Freshwater		0.0015 mg/l
Marine water 0.00015 mg/l		0.00015 mg/l
Freshwater sediment 3 mg/kg		3 mg/kg
Marine sediment		0.3 mg/kg
Soil		0.54 mg/kg
Sewage treatment plant		10 mg/l
8.2. Exposure controls		
Engineering controls	Ensure adequate ventilation, especially in confined areas.	
Personal protective equipment	t	
Eye/face protection	Wear safety glasses with side standard EN 166.	e shields (or goggles). Eye protection must conform to
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene <sup>™</sup> . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374	
Skin and body protection	None under normal use conditions.	
Respiratory protection		ion wear respiratory protection. Wear a respirator pe A/P2 filter or better. Ensure adequate ventilation,
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.	

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

#### **SECTION 9: Physical and chemical properties** 9.1. Information on basic physical and chemical properties **Physical state** Solid Appearance Paste See section 1 for more information Colour Odour Characteristic. **Odour threshold** No information available Property Values Remarks • Method Melting point / freezing point No data available None known Initial boiling point and boiling No data available None known range Flammability No data available None known Flammability Limit in Air None known Upper flammability or explosive No data available limits Lower flammability or explosive No data available limits Flash point No data available None known Autoignition temperature No data available None known **Decomposition temperature** None known No data available Not applicable. Insoluble in water. pН No data available pH (as aqueous solution) None known Kinematic viscosity $> 21 \text{ mm}^2/\text{s}$ @ 40 °C Dynamic viscosity No data available No data available. Product cures with Water solubility moisture Solubility(ies) No data available None known Partition coefficient No data available None known None known Vapour pressure No data available **Relative densitv** No data available None known Bulk Density No data available Liquid Density 1.24 g/ml Relative vapour density No data available None known

#### SILICONE OXIM QO16.100A (WHITE) Supercedes Date: 14-Mar-2022

SECTION 11: Toxicological	information
Hazardous decomposition products	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upo curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and release upon curing.
10.6. Hazardous decomposition p	products
Incompatible materials	Strong oxidising agents.
10.5. Incompatible materials	
Conditions to avoid	Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.
10.4. Conditions to avoid	
Possibility of hazardous reaction	
10.3. Possibility of hazardous rea	ctions
Sensitivity to mechanical impact Sensitivity to static discharge	None.
Explosion data	
Stability	Stable under normal conditions.
10.2. Chemical stability	
Reactivity	Product cures with moisture.
10.1. Reactivity	
SECTION 10: Stability and	reactivity
9.2.2. Other safety characteristics No information available	3
9.2.1. Information with regards to Not applicable	physical hazard classes
<u>9.2. Other information</u> Solid content (%) VOC content	No information available No data available
Particle Size Particle Size Distribution	No information available No information available

Information on likely routes of exposure

**Product Information** 

Inhalation	Based on available data, the classification criteria are not met.
Eye contact	Based on available data, the classification criteria are not met.

Skin contact	May cause sensitisation by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components).
Ingestion	Based on available data, the classification criteria are not met.
Symptoms related to the physical,	chemical and toxicological characteristics
Symptoms	Itching. Rashes. Hives.
Acute toxicity	
Numerical measures of toxicity	

### The following values are calculated based on chapter 3.1 of the GHS document<br/>ATEmix (oral)12,500.00 mg/kg

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus	>2.2 mg/L (Rattus) 1 h
		cuniculus)	
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus)4 h
2-Butanone, oxime	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
3-aminopropyltriethoxysilane	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rat, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT]	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	-

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Corrosive
Acute Dermal					
Irritation/Corrosion					

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	Eye			Non-irritant

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

Acute Eye Irritation/Corrosion			

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			
OECD Test No. 429: Skin	Mouse	Dermal	Not a skin sensitiser
Sensitisation: Local Lymph Node			
Assay			

2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		sensitising
Sensitisation: Local Lymph Node			
Assay			

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information 2-Butanone, oxime (96-29-7)			
Method	Species	Results	
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic	

Chemical name	European Union
2-Butanone, oxime	Carc. 1B

**Reproductive toxicity** 

Based on available data, the classification criteria are not met.

Chemical name	European Union	
Octamethylcyclotetrasiloxane [D4]	Repr. 2	

STOT - single exposure Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

#### 11.2.2. Other information

Other adverse effects

No information available.

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	=5000mg/L (96h,	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
2-Butanone, oxime 96-29-7	(72h,	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)		
3-aminopropyltriethoxy silane 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)		EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Octamethylcyclotetrasil oxane [D4] 556-67-2		LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)		EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus subspicatus) (OECD 201)	LC50 (96h) = 0.036 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

#### 12.2. Persistence and degradability

Persistence and degradability No information available.

#### Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining
			biodegradability are not
			applicable to inorganic
			substances

#### SILICONE OXIM QO16.100A (WHITE)

#### Octamethylcyclotetrasiloxane [D4] (556-67-2) 2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)

Method	Exposure time	Value	Results	
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable	
Mineralization in Surface Water -				
Simulation Biodegradation Test				

#### 12.3. Bioaccumulative potential

#### Bioaccumulation

#### Component Information

Chemical name	Partition coefficient
2-Butanone, oxime	0.65
3-aminopropyltriethoxysilane	1.7
Octamethylcyclotetrasiloxane [D4]	6.49
2-octyl-2H-isothiazol-3-one [OIT]	2.92

#### 12.4. Mobility in soil

Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

#### PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does
	not apply
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
2-Butanone, oxime	The substance is not PBT / vPvB
3-aminopropyltriethoxysilane	The substance is not PBT / vPvB
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT]	The substance is not PBT / vPvB

#### 12.6. Endocrine disrupting properties

#### **Endocrine disrupting properties** No information available.

Component Information		
Octamethylcyclotetrasiloxane [D4] (556-67-2)		
Method	Results	Species
Endocrine disrupting properties in accordance	Negative.	
with the criteria set out in Commission		
Delegated Regulation (EU) 2017/2100(3) or		
Commission Regulation (EU) 2018/605(4).		

#### 12.7. Other adverse effects

No information available.

#### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste from residues/unused Dispose of contents/container in accordance with local, regional, national, and

products	international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

#### SECTION 14: Transport information

#### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None
•	
IMDG	
14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk	Not applicable
according to IMO instruments	
-	
Air transport (ICAO-TI / IATA-DGR)	
14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable

#### Section 15: REGULATORY INFORMATION

None

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

**14.6 Special Provisions** 

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Reserved for industrial and professional use

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 2-octyl-2H-isothiazol-3-one [OIT]

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

### Persistent Organic Pollutants

Not applicable

#### National regulations

France

#### **Occupational Illnesses (R-463-3, France)**

Chemical name	French RG number
Silica, amorphous	RG 25
7631-86-9	
2-octyl-2H-isothiazol-3-one [OIT]	RG 5,RG 14,RG 15,RG 15bis,RG 20bis
26530-20-1	RG 2,RG 9,RG 14,RG 20,RG 34,RG 65

#### Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) strongly hazardous to water (WGK 3)

#### Netherlands

### List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
2-Butanone, oxime	Present
96-29-7	
Octamethylcyclotetrasiloxane [D4]	Fertility (Category 2)
556-67-2	

DenmarkRegistration number(s) (P-no.)No information availableNorwayRegistration number(s) (PRN-no.)No information available

#### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No

#### SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

Chemical Safety Assessment has been carried out for this mixture.

#### **SECTION 16: Other information**

Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

- H226 Flammable liquid and vapour
- H301 Toxic if swallowed
- H302 Harmful if swallowed
- H311 Toxic in contact with skin
- H312 Harmful in contact with skin
- H314 Causes severe skin burns and eye damage
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H330 Fatal if inhaled
- H336 May cause drowsiness or dizziness
- H350 May cause cancer
- H361f Suspected of damaging fertility
- H370 Causes damage to organs
- H373 May cause damage to organs through prolonged or repeated exposure
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

#### Notes assigned to an entry

**Note V:** If the substance is to be placed on the market as fibres (with diameter <  $3 \mu m$ , length >  $5 \mu m$  and aspect ratio ≥ 3:1) or particles of the substance fulfilling the WHO fibre criteria or as particles with modified surface chemistry, their hazardous properties must be evaluated in accordance with Title II of this Regulation, to assess whether a higher category (Carc. 1B or 1A) and/or additional routes of exposure (oral or dermal) should be applied

**Note W:** It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung

#### Notes relating to the classification and labelling of mixtures

**Note 10:** The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter  $\leq$  10 µm

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

- vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals
- STOT RE: Specific target organ toxicity Repeated exposure
- STOT SE: Specific target organ toxicity Single exposure
- EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

#### Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method

SILICONE OXIM QO16.100A (WHITE)

Supercedes Date: 14-Mar-2022

Acute inhalation toxicity - dust/mist	Calculation method	
Skin corrosion/irritation	Calculation method	
Serious eye damage/eye irritation	Calculation method	
Respiratory sensitisation	Calculation method	
Skin sensitisation	Calculation method	
mutagenicity	Calculation method	
Carcinogenicity	Calculation method	
Reproductive toxicity	Calculation method	
STOT - single exposure	Calculation method	
STOT - repeated exposure	Calculation method	
Acute aquatic toxicity	Calculation method	
Chronic aquatic toxicity	Calculation method	
Aspiration hazard	Calculation method	
Ozone	Calculation method	

#### Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA) European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA\_RAC) European Chemicals Agency (ECHA) (ECHA\_API) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) International Uniform Chemical Information Database (IUCLID) National Institute of Technology and Evaluation (NITE) NIOSH (National Institute for Occupational Safety and Health) Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By	Product Safety & Regulatory Affairs
Revision date	03-Aug-2022
Training Advice	No information available
Further information	No information available

#### This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### **End of Safety Data Sheet**