Den Braven

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking
· 1.1 Product identifier
 Trade name: <u>ZWALUW PRIMER-PF</u> 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
· Application of the substance / the mixture Sealant
 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: DEN BRAVEN Denariusstraat 11 4903 RC Oosterhout The Netherlands Tel: +31 (0)162-491000 Fax: +31 (0)162-421217 E-mail: info@denbraven.com Internet: www.denbraven.com
• Further information obtainable from: Product safety department.
info@denbraven.com
• 1.4 Emergency telephone number: info@denbraven.com
Tel.: +31 (0)162-491000
SECTION 2: Hazards identification
· 2.1 Classification of the substance or mixture
· Classification according to Regulation (EC) No 1272/2008
Classification according to Regulation (EC) No 1272/2008 GHS02 flame
GHS02 flame
GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin.
GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled.
GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin.
 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.
 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms Image: Contemport of the state of the sta
 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS02 GHS07 Signal word Warning Hazard-determining components of labelling:
 GHS02 flame Flam. Liq. 3 H226 Flammable liquid and vapour. GHS07 Acute Tox. 4 H312 Harmful in contact with skin. Acute Tox. 4 H332 Harmful if inhaled. Skin Irrit. 2 H315 Causes skin irritation. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS07 Signal word Warning

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

	(Contd. of page 1)
· Hazard statemen	ts
H226 Flam	mable liquid and vapour.
H312+H332 Harm	uful in contact with skin or if inhaled.
H315 Caus	es skin irritation.
· Precautionary sta	atements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	[or shower].
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	nation: TACTILE WARNING APPLICABLE FOR GENERAL PUBLIC
· 2.3 Other hazard	S
· Results of PBT an	nd vPvB assessment
· PBT: Not applical	ble.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 1330-20-7	xylene	10-<30%
EINECS: 215-535-7	🐼 Flam. Liq. 3, H226; 🗘 Acute Tox. 4, H312; Acute Tox. 4,	
Reg.nr.: 01-2119488216-32-xxxx	H332; Skin Irrit. 2, H315	
EC number: 919-446-0	Naphtha (petroleum), hydrodesulfurized heavy	1-<5%
Reg.nr.: 01-2119458049-33-xxxx	🚸 Flam. Liq. 3, H226; 🕹 Asp. Tox. 1, H304; 🚯 Aquatic Chronic	
-	2, H411; 🚯 STOT SE 3, H336	
	-1, -1 ,	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3) GB

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents:

- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

Pick up mechanically.

Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

Use only in well ventilated areas.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

(Contd. of page 2)

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

	(Contd. of page
	rol parameters
8	nts with limit values that require monitoring at the workplace:
1330-20-7	
	ort-term value: 441 mg/m ³ , 100 ppm ng-term value: 220 mg/m ³ , 50 ppm
	; BMGV
Ingredie	nts with biological limit values:
1330-20-7	
	550 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid
Addition	al information: The lists valid during the making were used as basis.
	sure controls
	protective equipment:
	protective and hygienic measures:
	ay from foodstuffs, beverages and feed.
	ely remove all soiled and contaminated clothing
	nds before breaks and at the end of work.
	ntact with the skin.
	ntact with the eyes and skin.
	ory protection: f brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure u
	tined respiratory protective device.
	on of hands:
1 ¹¹ 2 P	Protective gloves
The glove	e material has to be impermeable and resistant to the product/ the substance/ the preparation.
	of the glove material on consideration of the penetration times, rates of diffusion and the degradation
Material	
	bber, NBR
	ended thickness of the material: ≥ 0.35 mm
Penetrati	ion time of glove material >480min
Eye prote	
Т	ightly sealed goggles
SECTI	ON 9: Physical and chemical properties
9.1 Infor	mation on basic physical and chemical properties
	Information

- · General Information
- · Appearance: Form: Liquid **Colour:** Various colours · Odour: Characteristic · Odour threshold: Not determined.

(Contd. on page 5)

GB

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

	(Contd. of page 4)
· pH-value:	Undetermined.
[•] Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : Undetermined.
· Flash point:	23 - 60 °C
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	500 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.1 Vol %Undetermined.7 Vol %Undetermined.
· Vapour pressure:	Undetermined. Not determined.
 Density at 20 °C: Relative density Vapour density Evaporation rate 	0.93 g/cm ³ Not determined. Not determined. Not determined.
 Solubility in / Miscibility with water: 	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
 Solvent content: VOC (EC) VOC (EC) 9.2 Other information 	27.48 % 255.6 g/l No further relevant information available.

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

• 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

GB

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

(Contd. of page 5)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50 values relevant for classification:

1330-20-7	xylene	
0.1	I D CO	4 20

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	1,100 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- \cdot STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(Contd. on page 7)

GR

Version number 2

Revision: 14.03.2018

(Contd. of page 6)

Trade name: ZWALUW PRIMER-PF

Printing date 14.03.2018

Uncleaned packaging:
Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name · ADR · IMDG, IATA	1263 PAINT PAINT
· 14.3 Transport hazard class(es) · ADR, IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
 14.6 Special precautions for user Danger code (Kemler): EMS Number: Stowage Category 	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A
· 14.7 Transport in bulk according to Anr Marpol and the IBC Code	nex II of Not applicable.
· Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
• Transport category • Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

(Contd. on page 8)

Printing date 14.03.2018

Version number 2

Revision: 14.03.2018

Trade name: ZWALUW PRIMER-PF

(Contd. of page 7)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

- · Contact: Pascal Timmermans / Kees van Bemmel
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4
- Skin Irrit. 2: Skin corrosion/irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- Asp. Tox. 1: Aspiration hazard Category 1
- Aquatic Chronic 2: Hazardous to the aquatic environment long-term aquatic hazard Category 2
- * * Data compared to the previous version altered.