



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name ZWALUW PU-GUNFOAM

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Insulation foams

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Romania SRL
51, Rasaritului Street (DN7)
070000 Buftea
Ilfov
Romania
Phone: +40 372 833 300
Fax: +40 372 833 301
www.bostik.com

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Effects on or via lactation	Yes - (H362)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Category 3 Respiratory irritation	
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Chronic aquatic toxicity	Category 4 - (H413)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM

Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022

Revision Number 6.01

Contains Diphenylmethane-diisocyanate, isomers and homologues, Alkanes, C14-17, chloro



Signal word

Danger

Hazard statements

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H362 - May cause harm to breast-fed children

H373 - May cause damage to organs through prolonged or repeated exposure

H413 - May cause long lasting harmful effects to aquatic life

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P260 - Do not breathe mist/vapours/spray

P263 - Avoid contact during pregnancy/while nursing

P271 - Use only outdoors or in a well-ventilated area

P273 - Avoid release to the environment

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 - Store locked up

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

As from 24 August 2023 adequate training is required before industrial or professional use. Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. Type A1 according to standard EN 14387) is used.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. During transportation by car the cans should stand upright in the cargo space. When foaming the propellants are highly flammable.

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam.

PBT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Diphenylmethane-diisocyanate, isomers and homologues >25 - <40 %	618-498-9	9016-87-9	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	-	-	[7]
Alkanes, C14-17, chloro 20 - 25 %	287-477-0	85535-85-9	Lact. (H362) (EUH066) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) [H]	-	100	10	01-2119519269-33-XXXX
Dimethyl ether 5 - <10 %	204-065-8	115-10-6	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119472128-37-XXXX
Isobutane 5 - <10 %	200-857-2	75-28-5	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119485395-27-XXXX

Full text of H- and EUH-phrases: see section 16

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes
[H] - Substance has endocrine disrupting properties

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Diphenylmethane-diisocyanate, isomers and homologues	618-498-9	9016-87-9	-	-	1.5	-	-

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Chemical name	EC No	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Alkanes, C14-17, chloro	287-477-0	85535-85-9	-	-	-	-	-
Dimethyl ether	204-065-8	115-10-6	-	-	-	-	-
Isobutane	200-857-2	75-28-5	-	-	-	-	-

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No	SVHC candidates
Alkanes, C14-17, chloro	85535-85-9	X

Notes

See section 16 for more information

Chemical name	Notes
Dimethyl ether - 115-10-6	U
Isobutane - 75-28-5	C,U

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not use solvents or thinners to dissolve the material.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Difficulty in breathing.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supercedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation and skin contact. May cause sensitisation by skin contact.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO₂). Hydrogen chloride. Nitrogen oxides (NO_x). Hydrogen cyanide. Isocyanates.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Provide extract ventilation to points where emissions occur. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash it before reuse.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Keep out of the reach of children. Keep from freezing. Keep/store only in original container. Store in a dry place. Store in a closed container. Protect from moisture.

7.3. Specific end use(s)

Specific use(s)
Insulation foams.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Dimethyl ether 115-10-6	TWA: 1000 ppm TWA: 1920 mg/m ³

Derived No Effect Level (DNEL) No information available

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
 Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
 Revision Number 6.01

Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.7 mg/m ³	
worker Systemic health effects Long term	Dermal	47.9 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1894 mg/m ³	

Derived No Effect Level (DNEL)			
Alkanes, C14-17, chloro (85535-85-9)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	2 mg/m ³	
Consumer Long term Systemic health effects	Dermal	28.75 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.58 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	471 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Alkanes, C14-17, chloro (85535-85-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 µg/l
Marine water	0.2 µg/l
Microorganisms in sewage treatment	80 mg/l
Freshwater sediment	13 mg/kg dry weight
Marine sediment	2.6 mg/kg dry weight
Soil	11.9 mg/kg dry weight

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Soil	0.45 mg/kg dry weight
------	-----------------------

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Butyl rubber. Nitrile rubber. Glove thickness > 0.4 mm. The breakthrough time for the mentioned glove material is in general greater than 60 min. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	During spraying wear suitable respiratory equipment. In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better. AX.
Environmental exposure controls	Do not allow into any sewer, on the ground or into any body of water.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol Foam
Colour	Yellow
Odour	Characteristic. Slight.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	No data available
Initial boiling point and boiling range	Not applicable, Aerosol .	Not applicable, Aerosol
Flammability	Not applicable for liquids .	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	18.6 Vol%	
Lower flammability or explosive limits	1.7 Vol%	
Flash point	Not applicable, Aerosol .	Not applicable, Aerosol
Autoignition temperature	.	No data available
Decomposition temperature		No data available
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	No data available
Dynamic viscosity	No data available	No data available
Water solubility	Immiscible in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	No data available
Vapour pressure	6 - 7	bar @ 23 °C
Relative density	No data available	None known
Bulk Density	No data available	
Liquid Density	0.98 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

9.2. Other information

Solid content (%) No information available
VOC content No data available

9.2.1. Information with regards to physical hazard classes
Not applicable

9.2.2. Other safety characteristics
No information available

Minimum Ignition Temperature 235 Not applicable .
(°C)

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Heat, flames and sparks. Excessive heat. Do not freeze. Protect from moisture. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.
-----------------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-dust/mist) 3.08 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane-diisocyanate, isomers and homologues	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	=1.5 mg/L (Rattus) 4 h
Alkanes, C14-17, chloro	>4000 mg/kg (Rattus)	> 2000 mg/kg (Rattus)	-
Dimethyl ether	-	-	=164000 ppm (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Irritating to skin.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse		sensitising

Germ cell mutagenicity Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

Component Information
Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity Classification based on data available for ingredients. May cause harm to breast-fed children.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Alkanes, C14-17, chloro	Lact.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity May cause long lasting harmful effects to aquatic life. Cured foam has no C14-C17 chloroalkanes leaching in water for a maximum 20% C14-C17 chloroalkanes in mixture. Study: "Pulverized PU Foam HM23. Leaching study, Limit test" by Dr. Christine Jahns and sponsored by FEICA AISBL, 09.12.2014.

Method	Species	Endpoint type	Effective dose	Exposure time	Results	
OECD Test No. 202: Daphnia sp., Acute Immobilisation Test	Daphnia magna	EC50	1000 mg/L	48 hours	Harmless to aquatic organisms up to the tested concentration	
Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus)	CL50 (96h) >1000 mg/L (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

	subspicatus) (OECD 201)					
Alkanes, C14-17, chloro 85535-85-9	-	LC50: >500mg/L (48h, Leuciscus idus)	-	EC50 (48h) = 0.007 mg/l (Daphnia magna) OECD 202	100	10
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	> 4400 mg/L (Daphnia) (NEN 6501)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Alkanes, C14-17, chloro	7
Dimethyl ether	-0.18
Isobutane	2.8

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product contains substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment
Alkanes, C14-17, chloro	PBT & vPvB
Dimethyl ether	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB PBT assessment does not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
Waste codes / waste designations according to EWC / AVV	Waste codes should be assigned by the user based on the application for which the product was used.
European Waste Catalogue	08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous substances 17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2
Labels	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2, (D)
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	327, 625, 344, 190
Classification code	5F
Tunnel restriction code	(D)
Limited quantity (LQ)	1 L

IMDG

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, 2.1
14.5 Marine pollutant	NP
14.6 Special Provisions	63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ)	See SP277
EmS-No	F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	UN1950
14.2 Proper Shipping Name	Aerosols, flammable
14.3 Transport hazard class(es)	2.1
14.4 Packing group	Not regulated
Description	UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	A145, A167, A802
Limited quantity (LQ)	30 kg G
ERG Code	10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product contains one or more candidate substance(s) of very high concern (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Chemical name	CAS No
Alkanes, C14-17, chloro	85535-85-9

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56 74.
Diisocyanates	--	74

56

If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product

74 If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use"

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Diphenylmethane-diisocyanate, isomers and homologues	RG 62

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

9016-87-9	
Alkanes, C14-17, chloro 85535-85-9	RG 73
Dimethyl ether 115-10-6	RG 84
Isobutane 75-28-5	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Alkanes, C14-17, chloro 85535-85-9	Can be harmful via breastfeeding

Sweden

Occupational exposure limits AFS 2018:1

Special care should be applied for employees under the age of 18. Young people under the age of 18 may not carry out any work causing harmful exposure to this product. AFS 2012:3

AFS 2011: 19 - Chemical working environment risks (Amended and reprinted in AFS 2014: 43), §§37a-g

Denmark

Registration number(s) (P-no.) No information available

MAL-Code 1-3

AT-Guide C.0.1 August 2007: Limit values for substances and materials

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H220 - Extremely flammable gas

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H362 - May cause harm to breast-fed children

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM

Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022

Revision Number 6.01

Notes assigned to an entry

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)

Press. Gas (Liq.)

Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value

BGW

Biological limit value

Ceiling Maximum limit value

*

Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	On basis of test data
Chronic aquatic toxicity	On basis of test data
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGl(s))

International Uniform Chemical Information Database (IUCLID)

SAFETY DATA SHEET

ZWALUW PU-GUNFOAM
Supersedes Date: 22-Oct-2021

Revision date 01-Sep-2022
Revision Number 6.01

National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By	Product Safety & Regulatory Affairs
Revision date	01-Sep-2022
Revision note	SDS sections updated 12 14
Training Advice	AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet