

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX POLYFLEX HM WHITE

Date: 25.01.2022

Replaces: 22.03.2018 Ref:0256.5.BF/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX POLYFLEX HM WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited Dodworth Business Park Dodworth, Barnsley South Yorkshire, S75 3SP Tel: 01226 771600 Fax: 1226 771601 www.siroflex.co.uk

E-mail address info.siroflex.co.uk

1.4. Emergency telephone number

United Kingdom 01226 771600 (Office Hours Only)

Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl

1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction

EUH204 - Contains isocyanates. May produce an allergic reaction

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust

EUH210 - Safety data sheet available on request

Special provisions concerning the labelling of certain mixtures

Reserved for industrial and professional use. As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

United Kingdom - BE Page 1 / 16

 SX POLYFLEX HM WHITE
 Replaces: 22.03.2018

 Date: 25.01.2022
 Ref:0256.5.BF/DL

Causes mild skin irritation.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Xylene (reaction mass of ethylbenzene and xylene)	905-588-0	RR-45541-4	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	STOT RE 2 (H373):: C>=10%	01-2119488216- 32-xxxx
Titanium dioxide	236-675-5	13463-67-7	1 - <5	Carc. 2 (H351i)		01-2119489379- 17-XXXX
Aromatic Polyisocyanate	-	53317-61-6	0.1 - <1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)		[7]
Ethyl acetate	205-500-4	141-78-6	0.1 - <1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119475103- 46-XXXX
4,4'-Methylenediphenyl diisocyanate	202-966-0	101-68-8	0.01 - <0.1	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	01-2119457014- 47-XXXX

United Kingdom - BE Page 2 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

				Carc. 2 (H351) STOT SE 3 (H335) STOT RE 2 (H373)		
Reaction mass of Bis(1,2,2,6,6-pentameth yl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4- piperidyl sebacate	915-687-0	1065336-91- 5	0.01 - <0.1	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119491304- 40-XXXX
m-tolylidene diisocyanate	247-722-4	26471-62-5	0.01 - <0.1	Acute Tox. 1 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) Aquatic Chronic 3 (H412)	Resp. Sens. 1 :: C>=0.1%	01-2119454791- 34-XXXX

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. IF exposed or concerned: Get medical advice/attention.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a doctor.

Skin contactWash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never

give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Prolonged contact may cause redness and irritation.

United Kingdom - BE Page 3 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctorsTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

No information available.

Aldehydes. Hydrochloric Acid. Sulphur oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

United Kingdom - BE Page 4 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

Storage Conditions Protect from moisture.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure LimitsThis product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Polyvinyl chloride	-	TWA: 10 mg/m ³
9002-86-2		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Xylene (reaction mass of ethylbenzene and xylene)	TWA: 50 ppm	STEL: 100 ppm
RR-45541-4	TWA: 221 mg/m ³	STEL: 441 mg/m ³
	STEL: 100 ppm	TWA: 50 ppm
	STEL: 442 mg/m ³	TWA: 220 mg/m ³
	S*	Skin
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STFL: 12 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Xylene (reaction mass of eth	nylbenzene and xylene) (RR	-45541-4)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	221 mg/m³		
worker Long term Local health effects	Inhalation	221 mg/m³		
worker Short term Local health effects	Inhalation	442 mg/m³		
worker Long term Systemic health effects	Dermal	212 mg/kg bw/d		

Titanium dioxide (13463-67-7)			
Type	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	

United Kingdom - BE Page 5 / 16

Replaces: 22.03.2018 Ref:0256.5.BF/DL Date: 25.01.2022

SX POLYFLEX HM WHITE

worker	Inhalation	10 mg/m³	
Long term		_	
Local health effects			

Ethyl acetate (141-78-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Dermal	63 mg/kg bw/d	
Long term			
Systemic health effects			
worker	Inhalation	1468 mg/m³	
Short term		-	
Systemic health effects			
worker	Inhalation	734 mg/m³	
Long term			
Local health effects			
worker	Inhalation	1468 mg/m ³	
Short term		_	
Local health effects			
worker	Inhalation	734 mg/m³	
Long term			
Systemic health effects			

4,4'-Methylenediphenyl diisocyanate (101-68-8)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Short term Systemic health effects	Dermal	50 mg/kg bw/d		
worker Short term Systemic health effects	Inhalation	0.1 mg/m ³		
worker Short term Local health effects	Dermal	28700 μg/cm²		
worker Short term Local health effects	Inhalation	0.1 mg/m ³		
worker Long term Systemic health effects	Inhalation	0.05 mg/m ³		
worker Long term Local health effects	Inhalation	0.05 mg/m³		

sebacate (1065336-91-5) m-tolylidene diisocyanate (2	6471-62-5)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	0.035 mg/m³	
worker Short term Systemic health effects	Inhalation	0.14 mg/m³	
worker Long term Local health effects	Inhalation	0.035 mg/m³	
worker	Inhalation	0.14 mg/m ³	

United Kingdom - BE Page 6/16

 SX POLYFLEX HM WHITE
 Replaces: 22.03.2018

 Date: 25.01.2022
 Ref:0256.5.BF/DL

[
Short term		
Short term Local health effects		

Derived No Effect Level (DNEL)			
Xylene (reaction mass of eth	nylbenzene and xylene) (RR	-45541-4)	
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	65.3 mg/m³	
Consumer Short term Systemic health effects	Inhalation	260 mg/m³	
Consumer Long term Local health effects	Inhalation	65.3 mg/m³	
Consumer Short term Local health effects	Inhalation	260 mg/m³	
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	12.5 mg/kg bw/d	

Titanium dioxide (13463-67-7)					
Туре	Exposure route	Derived No Effect Level	Safety factor		
		(DNEL)	-		
Consumer	Oral	700 mg/kg bw/d			
Long term					
Systemic health effects					

Ethyl acetate (141-78-6)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer	Oral	4.5 mg/kg bw/d		
Long term				
Systemic health effects				
Consumer	Dermal	37 mg/kg bw/d		
Long term				
Systemic health effects				
Consumer	Inhalation	734 mg/m³		
Short term				
Systemic health effects				
Consumer	Inhalation	367 mg/m³		
Long term				
Local health effects				
Consumer	Inhalation	734 mg/m³		
Short term				
Local health effects				
Consumer	Inhalation	367 mg/m³		
Long term				
Systemic health effects				

4,4'-Methylenediphenyl diisocyanate (101-68-8)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer	Dermal	25 mg/kg bw/d		

United Kingdom - BE Page 7 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

Short term			
Systemic health effects			
Consumer	Inhalation	0.05 mg/m ³	
Short term		-	
Systemic health effects			
Consumer	Oral	20 mg/kg bw/d	
Short term			
Systemic health effects			
Consumer	Dermal	17200 μg/cm ²	
Short term			
Local health effects			
Consumer	Inhalation	0.05 mg/m ³	
Short term			
Local health effects			
Consumer	Inhalation	0.025 mg/m ³	
Long term			
Systemic health effects			
Consumer	Inhalation	0.025 mg/m ³	
Long term			
Local health effects			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.327 mg/l		
Marine water	0.327 mg/l		
Microorganisms in sewage treatment	6.58 mg/l		
Freshwater sediment	12.46 mg/kg dry weight		
Soil	2.31 mg/kg dry weight		

Titanium dioxide (13463-67-7)			
	In		
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Marine water	0.0184 mg/l		
Freshwater sediment	1000 mg/kg		
Freshwater	0.184 mg/l		
Marine sediment	100 mg/kg		
Soil	100 mg/kg		
Microorganisms in sewage treatment	100 mg/l		
Freshwater - intermittent	0.193 mg/l		

Ethyl acetate (141-78-6)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.26 mg/l		
Marine water	0.026 mg/l		
Freshwater sediment	1.25 mg/kg		
Marine sediment	0.125 mg/kg		
Soil	0.24 mg/kg		
Microorganisms in sewage treatment	650 mg/l		

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	1 mg/l		
Marine water	0.1 mg/l		
Soil	1 mg/kg dry weight		
Sewage treatment plant	1 mg/l		
Freshwater - intermittent	10 mg/l		

m-tolylidene diisocyanate (26471-62-5)

United Kingdom - BE Page 8 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.013 mg/l
Marine water	0.00125 mg/l
Microorganisms in sewage treatment	>1 mg/l
Soil	>1 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the

gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min.

Gloves must conform to standard EN 374

Skin and body protection Suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases

and vapours filter conforming to EN 14387.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White

Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

pH

pH (as aqueous solution)

Melting point / freezing point

Initial boiling point and boiling

No data available
No data available
Not applicable . °C

range

Flash point > 61 °C
Evaporation rate No data available
Flammability No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available Relative vapour density No data available Relative density No data available Water solubility No data available Solubility(ies) No data available **Partition coefficient** No data available No data available **Autoignition temperature Decomposition temperature** No data available 600000 mm²/s Kinematic viscosity Dynamic viscosity 600000 mPas **Explosive properties** No data available **Oxidising properties** No data available

United Kingdom - BE Page 9 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

9.2. Other information

Solid content (%)

No information available

VOC Content (%)

Density 1.23 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin

irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Prolonged contact may cause redness and irritation.

Numerical measures of toxicity

United Kingdom - BE Page 10 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 11,787.60 mg/kg ATEmix (inhalation-vapour) 283.20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	=3500 mg/kg (Rattus)	>10000 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h	
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l	
Aromatic Polyisocyanate 53317-61-6	LD50 >2000 mg/Kg (Rattus)		LC50 >3.820 mg/L (Rattus) 4h dust/mist	
Ethyl acetate 141-78-6	=5620 mg/kg (Rattus) > 18000 mg/kg (Or cuniculus) > 20 (Oryctolagus cun		LC0 29.3 mg/l air	
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	=1.5 mg/L (Rattus) 4 h	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-pi peridyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperi dyl sebacate 1065336-91-5	LD50 = 3230 mg/Kg (Rat) OECD 401	LD50 >3170 mg/Kg (Rat)		
m-tolylidene diisocyanate 26471-62-5	=3060 mg/kg (Rattus)	= 10000 mg/kg (Oryctolagus cuniculus)	=0.107 mg/L (Rattus) 4 h (Vapour)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2
4,4'-Methylenediphenyl diisocyanate 101-68-8	Carc. 2
m-tolylidene diisocyanate 26471-62-5	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

United Kingdom - BE Page 11 / 16

Replaces: 22.03.2018

Date: 25.01.2022 Ref:0256.5.BF/DL

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

SX POLYFLEX HM WHITE

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	EC50 (72hr) 2.2 mg/l (Selenastrum capricornutum)	LC50(96h) 2.6 mg/l (Oncorhynchus mykiss-OECD 203)	EC50 = 0.0084 mg/L 24 h	LC50(24h) 1 mg/l (Daphnia magna-OECD 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	•	•	-		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		
Reaction mass of	EC50 (72 h)	LC50 (96 h) 0,9	-	-	1	

United Kingdom - BE Page 12/16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

Bis(1,2,2,6,6-pentamet	, ,	mg/l,		
hyl-4-piperidyl)	(growth rate),	Brachydanio		
sebacate and Methyl	Desmodesmus	rerio (OECD		
1,2,2,6,6-pentamethyl-	subspicatus	203)		
4-piperidyl sebacate	(OECD 201)			
1065336-91-5				

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information Aromatic Polyisocyanate (53317-61-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready		biodegradation	34 % Not readily
Biodegradability: Manometric			biodegradable
Respirometry Test (TG 301 F)			

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent	28 days	0% biodegradation	Not readily biodegradable
Biodegradability: Modified MITI Test	-		
(II)			

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	3.15	25.9
Ethyl acetate 141-78-6	0.6	30
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51	200
m-tolylidene diisocyanate 26471-62-5	-	5

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Xylene (reaction mass of ethylbenzene and xylene)	The substance is not PBT / vPvB
RR-45541-4	
Titanium dioxide	The substance is not PBT / vPvB
13463-67-7	PBT assessment does not apply
Ethyl acetate	The substance is not PBT / vPvB
141-78-6	PBT assessment does not apply
4,4'-Methylenediphenyl diisocyanate	The substance is not PBT / vPvB
101-68-8	
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB

United Kingdom - BE Page 13 / 16

SX POLYFLEX HM WHITE Replaces: 22.03.2018
Date: 25.01.2022 Ref:0256.5.BF/DL

and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	
m-tolylidene diisocyanate 26471-62-5	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Marine pollutant
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP **14.6 Special Provisions** None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

United Kingdom - BE Page 14/16

Date: 25.01.2022 Ref:0256.5.BF/DL

Replaces: 22.03.2018

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

74 If product supplied to the industrial or professional users with total monomeric diisocyanates ≥ 0.1%, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

SX POLYFLEX HM WHITE

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H312 - Harmful in contact with skin

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

United Kingdom - BE Page 15/16

SX POLYFLEX HM WHITE Replaces: 22.03.2018 Date: 25.01.2022 Ref:0256.5.BF/DL

H336 - May cause drowsiness or dizziness

H351 - Suspected of causing cancer

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value Ceiling Skin designation

SVHC Substance(s) of Very High Concern

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals PBT Very Persistent and very Bioaccumulative (vPvB) Chemicals vPvB

STOT RE Specific target organ toxicity - Repeated exposure Specific target organ toxicity - Single exposure STOT SE

FWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 15-Sep-2021

Indication of changes

Revision note Not applicable.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE

INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 16/16