



DECLARATION OF PERFORMANCE

In accordance with Annex III of Regulation (EU) No 305/2011
(Construction Product Regulation)

DoP No S55001026-0010

1. Unique identification code of product-type:

SX PROFESSIONALS SEAL & FIX HYBRID

2. Type, batch or serial number or any other element allowing identification of the construction product as required to Article 11 (4):

Batch number: See product packaging

3. Intended use or uses of construction product, in accordance with applicable harmonized technical specification, as foreseen by the manufacturer:

Sealants for façade elements

Sealants for sanitary joints

Sealants for pedestrian walkways

EN 15651-1: F-EXT-INT-CC (CLASS 25HM)

EN 15651-3: S (CLASS XS3)

EN 15651-4: PW-EXT-INT-CC (CLASS 25HM)

4. Name, registered name or registered trade mark and contact address for the manufacture as required to Article 11 (5):

SIROFLEX LIMITED, DODWORTH BUSINESS PARK, DODWORTH, BARNSLEY, SOUTH YORKSHIRE, S75 3SP

5. Name and contact address of the authorized representative whose mandate covers the task specified in Article 12 (2): not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

System 3 for reaction to fire

7. In case of declaration of performance concerning a construction product covered by a harmonized standard:

DODWORTH BUSINESS PARK
DODWORTH BARNSLEY
SOUTH YORKSHIRE S75 3SP

SX PROFESSIONALS SEAL & FIX HYBRID - DoP No S55001026-0010

The notified body SKZ – TeConA GmbH (1213) performed the initial type testing according to EN 15651-1 / EN 15651-3 / EN 15651-4 and reaction to fire under system 3 and issued a test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: not relevant

9. Declared performance

Conditioning: Procedure B (according to ISO 8340)
 Substrate: Mortar M1 (with primer P03)
 Glass (without primer)
 Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained extension after water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

SX PROFESSIONALS SEAL & FIX HYBRID - DoP No S55001026-0010

Substrate: **Glass (without primer)**
 Anodised aluminium (without primer)

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Vertical flow resistance	≤ 3 mm	
Loss of volume	≤ 20 %	
Tensile properties at maintained extension after water immersion	NF	
Microbiological growth	3	
Durability	Pass	

SX PROFESSIONALS SEAL & FIX HYBRID - DoP No S55001026-0010

Substrate: Mortar M1 (with primer P03)

Essential characteristics	Performance	Harmonized technical
Reaction to fire	Class E	EN 15651-4:2012
Release of chemical dangerous to the environment and health	NPD (*)	
Water tightness and air tightness		
Tensile properties at maintained extension	NF	
Loss of volume	≤ 10 %	
Tear resistance	NF	
Adhesion / cohesion properties at maintained extension after 28 days water immersion	NF / change of secant modulus: ≤ 50 %	
Adhesion / cohesion properties at maintained extension after 28 days salt water immersion	NF	
Tensile properties (secant modulus) for use in cold climate areas (-30°C)	NR	
Tensile properties at maintained extension for use in cold climate areas (-30°C)	NF	
Durability	Pass	

(*) See material safety data sheet
 NPD: No Performance Determined
 NF: No Failure
 NR: Not required

Where pursuant in Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies: not relevant

SX PROFESSIONALS SEAL & FIX HYBRID - DoP No S55001026-0010

- 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.**

Signed for and on behalf of the manufacturer by



**Ashley Greenwood
HSE Manager
Siroflex Limited**

10/12/2015