

Hybrifix®

How to order

Hybrifix® is available in 290 ml cartridges packed per 12 in a box. To order your specific Hybrifix®, please find below the article and EAN codes:

Colour:	Article code:	EAN code:
White	10620500	8711595075206
Grey	10620300	8711595073882
Beige	10620100	8711595141352
Brown	10620200	8711595090667
Black	10620600	8711595090674



Centre of Excellence

Better results through Knowledge

Den Braven 's company payoff is "Better results through Knowledge". Our Centre of Excellence accumulates knowledge which provides her with the latest market insights, developments and trends.

This knowledge is shared within the Den Braven Group and amongst our customers and end-users.

This process enables our relations to achieve higher efficiency and better results. This is the true meaning of "Better results through Knowledge".

Visit our website to discover more about what the Centre of Excellence could mean for you!

denbraven.com



Den Braven



Hybrifix®

High quality hybrid sealant and adhesive

Universal sealant and construction adhesive suitable for a wide variety of applications

BETTER RESULTS THROUGH KNOWLEDGE

Hybrifix®

Product Descriptions

Hybrifix® is a high quality, professional and universal sealant and adhesive based on hybrid technology which cures under influence of humidity to form a durable elastic rubber.

Applications

Zwaluw Hybrifix has been especially developed as a universal sealant for connection joints in building and industry. Universal construction adhesive for bonding many building materials such as stone, concrete, glass, plasterboard, PU, uPVC, hard plastics, enamel, ceramic, copper, lead, zinc, aluminium, metals, stainless steel, HPL and cement fibre panels*, wood and paintsystems. Sealing and bonding in cold storage cells and in food area. *For bonding HPL and cement fibre panels see Technical Bulletin.

Hybrifix®

Certifications

EN 15651-1: F-EXT-INT-CC 20HM
EN 15651-3: S XS3
Emicode EC 1
ISEGA, M1

Technical Performances

Density	1,53 g/ml
Shore A harness	60°
Skin formation	10 minutes
Elongation at break	300%
100% modulus	1,35 Mpa
Tensile strength	2,20 Mpa
Curing time	2-3 mm/24 hours

Visit our website to download the full technical specifications of the Hybrifix®



Hybrifix®

High quality hybrid sealant and adhesive

Universal sealant and construction adhesive suitable for a wide variety of applications



- Durable, permanent elastic
- Universal bonding applicable
- Fast curing. Wet in wet applicable
- Isocyanates, solvents and silicones free
- No shrinkage and bubble free
- Good resistant to UV, weather and water
- Sanitary formulation
- ISEGA certified
- Emicode EC1



Visit Den Braven YouTube channel

Den Braven offers a wide variety of USP, Application and Commercial movies via here website and YouTube channel. Scan the below displayed QR Code to visit the product page of the original Hybrifix®:

