

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific
information for OEL

**BOSTIK FP401 ACRYLIC WHITE Supercedes Date**: 11-Mar-2020

Revision date 10-Mar-2021 Revision Number 4.01

\_\_\_\_\_

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product Name BOSTIK FP401 ACRYLIC WHITE

Pure substance/mixture Mixture

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

**Uses advised against**Not to be used in production of toys or childcare articles.

#### 1.3. Details of the supplier of the safety data sheet

#### **Company Name**

Bostik Benelux B.V. Denariusstraat 11 4903 RC Oosterhout The Netherlands Tel: + 31 162 491 000

E-mail address SDS.box-EU@bostik.com

#### 1.4. Emergency telephone number

Emergency Telephone No information available

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

## 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

#### Signal word

None

#### **Hazard statements**

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### **EU Specific Hazard Statements**

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

#### 2.3. Other hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

#### PBT & vPvB

Europe - EN Page 1/12

**BOSTIK FP401 ACRYLIC WHITE Supercedes Date:** 11-Mar-2020

Revision date 10-Mar-2021 Revision Number 4.01

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

substance considered to be very persistent nor very bioaccumulating (vPvB).

## **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Not applicable

#### 3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Ethylene glycol	203-473-3	107-21-1	0.1- <1	STOT RE 2 (H373) Acute Tox. 4 (H302)		01-2119456816- 28-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	220-120-9	2634-33-5	0.01 - <0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Acute Tox. 2 (H330) Aquatic Chronic 2 (H411) (M Factor Acute =1)	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute = 100 M Factor Chronic = 100	Eye Dam. 1 ::  C>=0.6% Irrit. 2 ::  0.06%<=C<0.6%  Skin Corr. 1C ::  C>=0.6%  Skin Irrit. 2 ::  0.06%<=C<0.6%  Skin Sens. 1 ::  C>=0.0015%	01-2120764691- 48-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

Europe - EN Page 2/12

Supercedes Date: 11-Mar-2020 **Revision Number** 4.01

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### **SECTION 4: First aid measures**

**BOSTIK FP401 ACRYLIC WHITE** 

#### 4.1. Description of first aid measures

**General advice** Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Revision date 10-Mar-2021

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with Ingestion

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** None known.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Note to doctors

## **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam. Suitable Extinguishing Media

Unsuitable extinguishing media Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon dioxide (CO2).

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

### SECTION 6: Accidental release measures

## 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Do not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

Europe - EN Page 3 / 12

Revision date 10-Mar-2021

**Revision Number** 4.01

•

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

**BOSTIK FP401 ACRYLIC WHITE** 

Supercedes Date: 11-Mar-2020

**Reference to other sections** See section 8 for more information. See section 13 for more information.

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Exposure Limits** Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon

curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)							
Ethylene glycol (107-21-1)	Ethylene glycol (107-21-1)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
worker Long term Systemic health effects	Dermal	106 mg/kg bw/d					
worker Long term Systemic health effects	Inhalation	35 mg/m³					

#### 1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)

Europe - EN Page 4/12

**BOSTIK FP401 ACRYLIC WHITE Supercedes Date:** 11-Mar-2020

Revision date 10-Mar-2021 Revision Number 4.01

Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	6.81 mg/m³	
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d	

Derived No Effect Level (DNEL)						
Ethylene glycol (107-21-1)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
Consumer Long term Systemic health effects	Dermal	53 mg/kg bw/d				
Consumer Long term Local health effects	Inhalation	7 mg/m³				

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
		1				
Consumer	Inhalation	1.2 mg/m <sup>3</sup>				
Long term						
Systemic health effects						
Consumer	Dermal	0.345 mg/kg bw/d				
Long term						
Systemic health effects						

# **Predicted No Effect Concentration** No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)				
Ethylene glycol (107-21-1)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	10 mg/l			
Marine water	1 mg/l			
Freshwater sediment	37 mg/kg dry weight			
Marine sediment	3.7 mg/kg dry weight			
Soil	1.53 mg/kg dry weight			
Microorganisms in sewage treatment	199.5 mg/l			

1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)				
Environmental compartment	Predicted No Effect Concentration (PNEC)			
Freshwater	4.03 μg/l			
Marine water	0.403 μg/l			
Sewage treatment plant	1.03 mg/l			
Freshwater sediment	49.9 μg/l			
Marine sediment	4.99 μg/l			
Soil	3 mg/kg dry weight			

#### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

**Hand protection** Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Europe - EN Page 5/12

Supercedes Date: 11-Mar-2020 Revision Number 4.01

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

Revision date 10-Mar-2021

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

**BOSTIK FP401 ACRYLIC WHITE** 

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

#### SECTION 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

Physical stateLiquidAppearancePasteColourWhiteOdourCharacteristic

Odour threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in waterMelting point / freezing point No data available

Initial boiling point and boiling 100 °C

range

Flash point > 100 °C
Evaporation rate No data available

Flammability Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data availableRelative densityNo data availableWater solubilityImmiscible in waterSolubility(ies)No data availablePartition coefficientNo data available

Autoignition temperature 420 °C

Decomposition temperatureNo data availableKinematic viscosityNo data availableDynamic viscosityNo data availableExplosive propertiesNo data availableOxidising propertiesNo data available

9.2. Other information

Solid content (%) No information available

VOC Content (%) 18.1 g/L / 0.9 % European directive n°2010/75/UE

Liquid Density 1.59 g/cm<sup>3</sup>

## **SECTION 10: Stability and reactivity**

10.1. Reactivity

**Reactivity** Product cures with moisture.

10.2. Chemical stability

Europe - EN Page 6/12

Supercedes Date: 11-Mar-2020 **Revision Number** 4.01

Stable under normal conditions. **Stability** 

**Explosion data** 

Sensitivity to mechanical

**BOSTIK FP401 ACRYLIC WHITE** 

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Protect from moisture. Exposure to air or moisture over prolonged periods. Do not Conditions to avoid

freeze. Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materials Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 10-Mar-2021

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Information on likely routes of exposure

**Product Information** 

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** No information available.

Numerical measures of toxicity

**Acute toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document

**Component Information** 

	Inhalation LC50
Ethylene glycol ATE 500 mg/kg = 10600 mg/kg (Rattus) =	
107-21-1 9530 μL/kg (Oryctolagus	
cuniculus)	
1,2-benzisothiazol-3(2H)-one =670 mg/kg (Rattus) LD50 > 2000 mg/kg (Rattus)	

Europe - EN Page 7/12

**BOSTIK FP401 ACRYLIC WHITE Supercedes Date:** 11-Mar-2020

Revision date 10-Mar-2021 Revision Number 4.01

2634-33-5			
reaction mass of	=53 mg/kg (Rattus)	LD50 = 87.12 mg/kg	
5-chloro-2-methyl-2H-isothiazo		(Oryctolagus cuniculus)	
I-3-one and			
2-methyl-2H-isothiazol-3-one			
(3:1) [C(M)IT/MIT]			
55965-84-9			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

#### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 11.2.2. Other information

Other adverse effects No information available.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Ecotoxicity .

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Ethylene glycol	EC50: 6500 -	LC50 96 h =	EC50 = 10000	EC50:		
107-21-1	13000mg/L	16000 mg/L	mg/L 16 h	=46300mg/L		
	(96h,	(Poecilia	EC50 = 620	(48h, Daphnia		
	Pseudokirchneri	reticulata static)	mg/L 30 min	magna)		

Europe - EN Page 8/12

BOSTIK FP401 ACRYLIC WHITE Supercedes Date: 11-Mar-2020 Revision date 10-Mar-2021 Revision Number 4.01

	ella subcapitata)		EC50 = 620.0 mg/L 30 min			
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	1
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner	EC50 (96h) = 0.22 mg/L (Oncorhynchus mykiss) (OECD 211)	-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

#### 12.2. Persistence and degradability

**Persistence and degradability** No information available.

12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### **Component Information**

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Ethylene glycol	-1.36	-
107-21-1		
1,2-benzisothiazol-3(2H)-one [BIT]	0.7	6.95
2634-33-5		
reaction mass of	-	3.16
5-chloro-2-methyl-2H-isothiazol-3-one and		
2-methyl-2H-isothiazol-3-one (3:1)		
[C(M)IT/MIT]		
55965-84-9		

### 12.4. Mobility in soil

**Mobility in soil** No information available.

### 12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment . The product does not contain any substance(s) classified as PBT or vPvB.

Chemical name	PBT and vPvB assessment	
Ethylene glycol	The substance is not PBT / vPvB	
107-21-1	PBT assessment does not apply	
1,2-benzisothiazol-3(2H)-one [BIT] 2634-33-5	The substance is not PBT / vPvB	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] 55965-84-9	The substance is not PBT / vPvB	

#### 12.6. Other adverse effects

Other adverse effects No information available.

Europe - EN Page 9 / 12

.

Supercedes Date: 11-Mar-2020 Revision Number 4.01

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**BOSTIK FP401 ACRYLIC WHITE** 

Waste from residues/unused

products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

Revision date 10-Mar-2021

regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

#### SECTION 14: Transport information

## Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

#### **IMDG**

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine pollutantNP14.6 Special ProvisionsNone

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

#### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
14.5 Environmental hazards
Not regulated Not regulated Not regulated Not applicable

14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

**SVHC: Substances of Very High Concern for Authorisation:** 

Europe - EN Page 10/12

**BOSTIK FP401 ACRYLIC WHITE Supercedes Date:** 11-Mar-2020

Revision date 10-Mar-2021 Revision Number 4.01

\_\_\_\_\_

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Diisononyl phthalate	28553-12-0	52[a].

52

Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

#### Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide: Contains C(M)IT/MIT (3:1). May produce an allergic reaction

#### Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

## National regulations

#### <u>France</u>

#### Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Ethylene glycol	RG 84
107-21-1	RG 5,RG 14,RG 15,RG 15bis,RG 20bis
1,2-benzisothiazol-3(2H)-one [BIT]	RG 65
2634-33-5	

#### Germany

## Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

#### Netherlands

# List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Denmark

Registration number(s) (P-no.) No information available

**Norway** 

Registration number(s) (PRN-no.) No information available

### 15.2. Chemical safety assessment

Europe - EN Page 11/12

Revision date 10-Mar-2021

Supercedes Date: 11-Mar-2020 Revision Number 4.01

\_\_\_\_\_

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

#### **SECTION 16: Other information**

**BOSTIK FP401 ACRYLIC WHITE** 

#### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H310 - Fatal in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
\* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 10-Mar-2021

Indication of changes

**Revision note** SDS sections updated, 1.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet** 

Europe - EN Page 12/12