

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Product Name	SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC
Pure substance/mixture	Mixture
1.2. Relevant identified uses of the	e substance or mixture and uses advised against
Recommended use	Sealant
Uses advised against	None known
1.3. Details of the supplier of the s	afety data sheet
Company Name	
Siroflex Limited Dodworth Business Park, Dodworth Barnsley, South Yorkshire S75 3SP Tel: +44 (1226) 771600 Fax: +44 (1226) 771601 www.sirof	lex.co.uk
E-mail address	info.siroflex@bostik.com
1.4. Emergency telephone number	
United Kingdom	+44 (1226) 771600 (Office Hours Only)
Ireland	NPIC - National Poison Information Centre Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week) Healthcare Professionals: +353 (01) 8092566 (24 hour service)
Europe	112
SECTION 2: Hazards identif	

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] & 1,2-benzisothiazol-3(2H)-one [BIT]. May produce an allergic reaction EUH210 - Safety data sheet available on request

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

2.3. Other hazards

No information available.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Silica, amorphous	231-545-4	7631-86-9	0.1 - <0.5	[B]	-	01-2119379499- 16-XXXX
Sodium hydroxide	(011-002-00- 6) 215-185-5	1310-73-2	0.1 - <0.3	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Met. Corr. 1 (H290)	Eye Irrit. 2 :: 0.5%<=C<2% Eye Dam. 1 :: C>=2% Skin Corr. 1A :: C>=5% Skin Corr. 1B :: 2%<=C<5% Skin Irrit. 2 :: 0.5%<=C<2%	01-2119457892- 27-XXXX
1,2-benzisothiazol-3(2H) -one [BIT]	6) 220-120-9	2634-33-5	0.01 - < 0.05	Acute Tox. 4 (H302) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	Skin Sens. 1 :: C>=0.05%	01-2120761540- 60-XXXX
reaction mass of 5-chloro-2-methyl-2H-iso thiazol-3-one and 2-methyl-2H-isothiazol-3 -one (3:1) [C(M)IT/MIT]	611-341-5	55965-84-9	<0.0015	Acute Tox. 3 (H301) Acute Tox. 2 (H310) Acute Tox. 2 (H330) Skin Corr. 1C (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1	Eye Dam. 1 :: C>=0.6% Eye Irrit. 2 :: 0.06%<=C<0.6% Skin Corr. 1C :: C>=0.6% Skin Irrit. 2 :: 0.06%<=C<0.6% Skin Sens. 1 :: C>=0.0015%	01-2120764691- 48-XXXX

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

		(H410)	

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes [B] - Substance with a Community workplace exposure limit

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	В
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] - 55965-84-9	

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.			
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.			
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.			
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.			
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.			
4.2. Most important symptoms and	d effects, both acute and delayed			
Symptoms	No information available.			
4.3. Indication of any immediate m	edical attention and special treatment needed			
Note to doctors	No information available.			
SECTION 5: Firefighting me	asures			
5.1. Extinguishing media				
Suitable Extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
Unsuitable extinguishing media	No information available.			
5.2. Special hazards arising from t	he substance or mixture			
Specific hazards arising from the chemical	No information available.			

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

Hazardous combustion p	oducts Silicon dioxide.
------------------------	-------------------------

5.3. Advice for firefighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures				
Personal precautions	Ensure adequate ventilation.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2. Environmental precautions				
Environmental precautions	See Section 12 for additional Ecological Information.			
6.3. Methods and material for cont	ainment and cleaning up			
Methods for containment	Do not scatter spilled material with high pressure water streams.			
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
6.4. Reference to other sections				
Reference to other sections	See section 8 for more information. See section 13 for more information.			
SECTION 7: Handling and st	orage			
7.1. Precautions for safe handling				
	_			
Advice on safe handling	Ensure adequate ventilation.			
-				
Advice on safe handling	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.			
Advice on safe handling General hygiene considerations	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice.			
Advice on safe handling General hygiene considerations 7.2. Conditions for safe storage, in	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. cluding any incompatibilities			
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. cluding any incompatibilities Keep from freezing.			
Advice on safe handling General hygiene considerations <u>7.2. Conditions for safe storage, in</u> Storage Conditions Recommended storage temperature	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. cluding any incompatibilities Keep from freezing.			
Advice on safe handling General hygiene considerations 7.2. Conditions for safe storage, in Storage Conditions Recommended storage temperature 7.3. Specific end use(s) Specific use(s) Sealant.	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. cluding any incompatibilities Keep from freezing.			
Advice on safe handling General hygiene considerations 7.2. Conditions for safe storage, in Storage Conditions Recommended storage temperature 7.3. Specific end use(s) Specific use(s) Sealant.	Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. cluding any incompatibilities Keep from freezing. Do not freeze. Keep at temperatures between 5 and 35 °C.			

8.1. Control parameters

Exposure Limits

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

Chemical name	European Union	United Kingdom
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m ³	TWA: 6 mg/m ³ TWA: 2.4 mg/m ³ TWA: 0.1 mg/m ³ STEL: 18 mg/m ³ STEL: 7.2 mg/m ³ STEL: 0.3 mg/m ³
Sodium hydroxide 1310-73-2	-	STEL: 2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	6.81 mg/m³		
worker Long term Systemic health effects	Dermal	0.966 mg/kg bw/d		

Derived No Effect Level (DNEL)				
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-5)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	1.2 mg/m³		
Consumer Long term Systemic health effects	Dermal	0.345 mg/kg bw/d		

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)			
1,2-benzisothiazol-3(2H)-one [BIT] (2634-33-	5)		
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	4.03 µg/l		
Marine water	0.403 µg/l		
Sewage treatment plant	1.03 mg/l		
Freshwater sediment	49.9 µg/l		
Marine sediment	4.99 µg/l		
Soil	3 ma/kg dry weight		

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment Eye/face protection Skin and body protection

Tight sealing safety goggles. Suitable protective clothing.

Environmental exposure controls No information available.

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical		
Physical state	Solid	
Appearance	Paste	
Colour	See section 1 for more information	
Odour	Characteristic.	
Odour threshold	No information available	
D	Male and	B
Property	Values	Remarks • Method
Melting point / freezing point	$= 0 ^{\circ}C$	
Initial boiling point and boiling	= 100 °C	
range		
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive	No data available	
limits		
Lower flammability or explosive	No data available	
limits		
Flash point	approx No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature		None known
рН	7 - 9	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm²/s	
Dynamic viscosity	No data available	
Water solubility	Soluble in water.	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Liquid Density	0.71	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	
9.2. Other information		
Solid content (%)	No information available	
VOC content	No data available	ailable
	140 Gala avi	

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity		
10.1. Reactivity		
Reactivity	No information available.	
10.2. Chemical stability		
Stability	Stable under normal conditions.	
Explosion data		

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

Sensitivity to mechanical	None.			
impact Sensitivity to static discharge None.				
10.3. Possibility of hazardous reac	tions			
Possibility of hazardous reactions	None under normal processing.			
10.4. Conditions to avoid				
Conditions to avoid	Do not freeze.			
10.5. Incompatible materials				
Incompatible materials	None known based on information supplied.			
10.6. Hazardous decomposition products				
Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.			
SECTION 11: Toxicological i	nformation			
11.1. Information on hazard class	es as defined in Regulation (EC) No 1272/2008			
Information on likely routes of exp	osure			
Product Information				
Inhalation	Based on available data, the classification criteria are not met.			
Eye contact	Based on available data, the classification criteria are not met.			
Skin contact	Based on available data, the classification criteria are not met.			

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms N	lo information available.
------------	---------------------------

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h	
Sodium hydroxide	=325 mg/kg (Rattus)	= 1350 mg/kg (Oryctolagus cuniculus)	-	
1,2-benzisothiazol-3(2H)-one [BIT]	=670 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus)	-	
reaction mass of 5-chloro-2-methyl-2H-isothiazo	= 53 mg/kg (Rat)	LD50 = 87.12 mg/kg (Oryctolagus cuniculus)	= 0.33 mg/L (Rat) 4h	

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

I-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	
Delayed and immediate effects as	well as chronic effects from short and long-term exposure
Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met.
Respiratory or skin sensitisation	Based on available data, the classification criteria are not met.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
11.2. Information on other hazard	<u>s</u>
11.2.1. Endocrine disrupting prop	perties
Endocrine disrupting properties	No information available.
11.2.2. Other information	
Other adverse effects	No information available.
SECTION 12: Ecological infe	ormation

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Silica, amorphous	EC50: =440mg/L	LC50:	-	EC50:		
7631-86-9	(72h,	=5000mg/L (96h,		=7600mg/L (48h,		
	Pseudokirchneri	Brachydanio		Ceriodaphnia		
	ella subcapitata)	rerio)		dubia)		
Sodium hydroxide	-	LC50:	-	-		
1310-73-2		=45.4mg/L (96h,				

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

		Oncorhynchus mykiss)				
1,2-benzisothiazol-3(2 H)-one [BIT] 2634-33-5	EC50 3Hr 13mg/l (activated sludge) (OECD 209)	LC50 (96hr) 2.15 mg/l Cyprinodon variegatus EPA 540/9-85-006		EC50(48hr) 2.94 mg/l (Daphnia Magna) OECD 202	1	
reaction mass of 5-chloro-2-methyl-2H-is othiazol-3-one and 2-methyl-2H-isothiazol- 3-one (3:1) [C(M)IT/MIT] 55965-84-9	(Pseudokirchner		-	EC50 (48h) =0.1 mg/L (Daphnia magna) (OECD 202)	100	100

12.2. Persistence and degradability

Persistence and degradability

No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time Value Results		Results
			The methods for determining
			biodegradability are not
			applicable to inorganic
			substances

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT] (55965-84-9)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	Not readily biodegradable
Biodegradability: CO2 Evolution Tes	st		
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
1,2-benzisothiazol-3(2H)-one [BIT]	0.7
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and	0.7
2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does
	not apply
Sodium hydroxide	The substance is not PBT / vPvB PBT assessment does
	not apply
1,2-benzisothiazol-3(2H)-one [BIT]	The substance is not PBT / vPvB
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) [C(M)IT/MIT]	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Note:

Keep from freezing.

Land transport (ADR/RID) 14.1 UN number or ID number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special precautions for user Special Provisions	Not regulated Not regulated Not regulated Not regulated Not applicable None	
IMDG		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special precautions for user		
Special Provisions	None	
14.7 Maritime transport in bulk		
according to IMO instruments		
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable		
Air transport (ICAO-TI / IATA-DGR)		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Environmental hazards	Not applicable	
14.6 Special precautions for user		

Special Provisions None

Section 15: REGULATORY INFORMATION

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

Contains a biocide : Contains C(M)IT/MIT (3:1). May produce an allergic reaction

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

- H301 Toxic if swallowed
- H302 Harmful if swallowed
- H310 Fatal in contact with skin
- H314 Causes severe skin burns and eye damage
- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage

SX DECORATORS INSTANTLY PAINTABLE CAULK ACRYLIC Date: 18.04.2024

Replaces: 06.03.2023 Ref: 0328.6.BB/DL

H330 - Fatal if inhaled

- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects

H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note B: Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: 'nitric acid ... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis

Legend	
TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by
	Road
IMDG	International Maritime Dangerous Goods (IMDG)
ΙΑΤΑ	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	27-Mar-2023
Indication of changes	
Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet