

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022

Revision date 07-Jun-2022 **Revision Number** 1

SECTION 1: Identification of the substance/mixture and of the comp	pany/undertak	king
--	---------------	------

1.1. Product identifier							
Product Name	ZWALUW SILICONE-100	1U BROWN					
Pure substance/mixture	Mixture	Mixture					
1.2. Relevant identified uses	of the substance or mixture an	d uses advised against					
Recommended use	Sealant						
Uses advised against	None known.						
1.3. Details of the supplier of	the safety data sheet						
Company Name Bostik Benelux B.V. Denariusstraat 11 4903 RC Oosterhout The Netherlands Tel: + 31 162 491 000							
E-mail address	SDS.box-EU@bostik.com						
1.4. Emergency telephone nu	mber						
Emergency Telephone	112						
SECTION 2: Hazards ide	ntification						
2.1. Classification of the subs	tance or mixture						
Regulation (EC) No 1272/2008							
Chronic aquatic toxicity		Catego	ory 3 - (H412)				

2.2. Label elements

Hazard statements

H412 - Harmful to aquatic life with long lasting effects

EU Specific Hazard Statements

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] & Dimethylbis[(1-oxoneodecyl)oxy]stannane. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P273 - Avoid release to the environment

P501 - Dispose of contents/ container to an approved waste disposal plant

2.3. Other hazards

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No.	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	(long-ter m)	REACH registration number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics >25 - <40 %	934-956-3	RR-100252-4	Asp. Tox. 1 (H304)	-	-	-	01-2119827000- 58-XXXX
Silica, amorphous 5 - <10 %	231-545-4	7631-86-9	[B]	-	-	-	01-2119379499- 16-XXXX
Triacetoxy(propyl)silane 1 - <2.5 %	241-816-9	17865-07-5	Skin Corr. 1B (H314) (EUH071)	-	-	-	01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate 1 - <2.5 %	224-221-9	4253-34-3	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)	-	-	-	01-2119962266- 32-XXXX
Octamethylcyclotetrasilo xane [D4] 0.01 - <0.05 %	209-136-7	556-67-2	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) [G]	-	-	10	01-2119529238- 36-XXXX
4,5-dichloro-2-octyl-2H-is othiazol-3-one [DCOIT] 0.01 - <0.05 %	264-843-8	64359-81-5	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) (EUH071)	Skin Irrit. 2 :: 0.025%<=C<5% Eye Irrit. 2 :: 0.025%<=C<3% Skin Sens. 1A :: C>=0.0015%	100	100	-
Dimethylbis[(1-oxoneode cyl)oxy]stannane 0.01 - <0.05 %	273-028-6	68928-76-7	Skin Irrit. 2 (H315) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Aquatic Chronic 3 (H412)	-	-	-	01-2120770324- 57-xxxx

Substances identified by a number starting "RR-" in the CAS-field are substances for which there is no CAS# used in EU and we use an internal numbering system to track within our SDS software

Air contaminants formed when using the substance or mixture as intended

Chemical name	EC No	CAS No	Classification according to Regulation (EC) No. 1272/2008 [CLP]		M-Factor	M-Factor (long-term)	REACH registration number
Acetic acid	200-580-7	64-19-7	Skin Corr. 1A	Eye Irrit. 2 ::	-	-	01-2119475328

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

64-19-7	(H314)	10%<=C<25%		-30-XXXX
	Flam. Liq. 3	Skin Corr. 1A ::		
	(H226)	C>=90%		
		Skin Corr. 1B ::		
		25%<=C<90%		
		Skin Irrit. 2 ::		
		10%<=C<25%		

Full text of H- and EUH-phrases: see section 16

Classification according to Regulation (EC) No. 1272/2008 [CLP] - Notes [B] - Substance with a Community workplace exposure limit

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No	CAS No	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	-	-	-	-	-
Silica, amorphous	231-545-4	7631-86-9	-	-	-	-	-
Triacetoxy(propyl)silane	241-816-9	17865-07-5	-	-	-	-	-
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1600	-	-	-	-
Octamethylcyclotetrasil oxane [D4]	209-136-7	556-67-2	-	-	-	-	-
4,5-dichloro-2-octyl-2H- isothiazol-3-one [DCOIT]	264-843-8	64359-81-5	567 +	-	0.16+	0.16+	0.16+
Dimethylbis[(1-oxoneod ecyl)oxy]stannane	273-028-6	68928-76-7	892	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Consult an ophthalmologist.
Skin contact	In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and water.
Ingestion	Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022

4.2. Most important symptoms and	effects, both acute and delayed
Symptoms	None known.
4.3. Indication of any immediate m	edical attention and special treatment needed
Note to doctors	Treat symptomatically.
SECTION 5: Firefighting mea	asures
5.1. Extinguishing media	
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.
Unsuitable extinguishing media	Full water jet.
5.2. Special hazards arising from the	he substance or mixture
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.
Hazardous combustion products	Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of irritating and toxic gases and vapours.
5.3. Advice for firefighters	
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.
SECTION 6: Accidental relea	ase measures
6.1. Personal precautions, protecti	ve equipment and emergency procedures
Personal precautions	Do not get in eyes, on skin, or on clothing. Use personal protective equipment as required. Ensure adequate ventilation.
For emergency responders	Use personal protection recommended in Section 8.
6.2. Environmental precautions	
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.
6.3. Methods and material for conta	ainment and cleaning up
Methods for containment	Do not scatter spilled material with high pressure water streams.
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
6.4. Reference to other sections	
Reference to other sections	See section 8 for more information. See section 13 for more information.
SECTION 7: Handling and st	orage

SECTION 7: Handling and storage

7.1. Precautions for safe handling

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

Advice on safe handling	Ensure adequate ventilation.
General hygiene considerations	Do not eat, drink or smoke when using this product. Wash hands before breaks and after work. Take off all contaminated clothing and wash it before reuse.
7.2. Conditions for safe storage, inc	cluding any incompatibilities
Storage Conditions	Protect from moisture. Keep away from food, drink and animal feedingstuffs.
Recommended storage temperature	Keep at temperatures between 10 and 35 °C.
7.3. Specific end use(s)	
Specific use(s) Sealant.	
Risk Management Methods (RMM)	The information required is contained in this Safety Data Sheet.
Other information	Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	TWA/8h
RR-100252-4	5mg/m³
	STEL/15 mins 10mg/m ³
Silica, amorphous	TWA: 0.1 mg/m ³
7631-86-9	
Acetic acid	TWA: 25 mg/m ³
64-19-7	TWA: 10 ppm
	STEL: 50 mg/m ³
	STEL: 20 ppm

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)						
Octamethylcyclotetrasiloxane	Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor			
worker	Inhalation	73 mg/m³				
Long term Systemic health effects						

Derived No Effect Level (DNEL)					
Octamethylcyclotetrasiloxane	D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	13 mg/m³			
Consumer Long term	Oral	3.7 mg/kg bw/d			

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

Systemic health effects							

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)					
Octamethylcyclotetrasiloxane [D4] (556-67-2)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.0015 mg/l				
Marine water	0.00015 mg/l				
Freshwater sediment	3 mg/kg				
Marine sediment	0.3 mg/kg				
Soil	0.54 mg/kg				
Sewage treatment plant	10 mg/l				

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166. Wear suitable gloves, Recommended Use:, Neoprene™, Nitrile rubber, Butvl rubber, Hand protection Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374 Skin and body protection None under normal use conditions. **Respiratory protection** In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas. **Recommended filter type:** Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical Physical state Appearance	<mark>and chemical properties</mark> Solid Paste	
Colour	See section 1 for more information	
Odour	Acetic acid.	
Odour threshold	No information available	
Property	Values	Remarks • Method
Melting point / freezing point	No data available	None known
Initial boiling point and boiling	No data available	None known
range		
Flammability	Not applicable for liquids .	
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive	No data available	
limits	400.00	
Flash point	> 100 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	Na data availabla	Not applicable Insoluble in water
pH (as aqueous solution) Kinematic viscosity	No data available > 21 mm ² /s	None known
Milematic viscosity	> 21 1111173	

None known None known None known None known

None known

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022 Revision date 07-Jun-2022 Revision Number 1

Dynamic viscosity	No data available
Water solubility	No data available Product cures with
	moisture
Solubility(ies)	No data available
Partition coefficient	No data available
Vapour pressure	No data available
Relative density	No data available
Bulk Density	No data available
Liquid Density	0.97
Relative vapour density	No data available
Particle characteristics	
Particle Size	No information available
Particle Size Distribution	No information available

9.2. Other information VOC Content (%)

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Product cures with moisture. Reactivity 10.2. Chemical stability Stability Stable under normal conditions. **Explosion data** Sensitivity to mechanical None. impact Sensitivity to static discharge None. 10.3. Possibility of hazardous reactions Possibility of hazardous reactions None under normal processing. 10.4. Conditions to avoid Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition. 10.5. Incompatible materials Incompatible materials Strong oxidising agents. 10.6. Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions. Hazardous decomposition products

SECTION 11: Toxicological information

Supercedes Date: 07-Jun-2022

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Eye contact	Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met.			
Skin contact				
Skin contact	Based on available data, the classification criteria are not met. May cause sensitisation in susceptible persons.			
Ingestion	Based on available data, the classification criteria are not met.			
Symptoms related to the physical, chemical and toxicological characteristics				

Symptoms

No information available.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20,	LD50 > 5000 mg/kg (Rattus)	LD50 > 3160 mg/kg	LC50 Inhalation(4h) >5266
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	MG/M3 (Rattus)
< 0.03% aromatics		OECD 402	
Silica, amorphous	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Silanetriol, methyl-, triacetate	LD50 = 1600 mg/kg (Rattus) OECD 401	-	-
Octamethylcyclotetrasiloxane [D4]	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT]	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h
Dimethylbis[(1-oxoneodecyl)ox y]stannane	LD50 =892 mg/Kg (Rattus) (OECD 401)	LD50 >2000 mg/Kg (rattus)	_

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation

The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal			Non-irritant
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

Serious eye damage/eye irritation

n By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void). The assessment of the result of testing was done in accordance with the guideline of the Commission 92/ 69/ EEC.

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye			Non-irritant
	Rabbit	eye		6 days	Product score
					<=1

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022

			Non-irritant			
Respiratory or skin sensitisa		proposed, based on conclusive May cause sensitisation in sus	e negative data. OECD Test No. ceptible persons.			
Method	Species	Exposure route	Results			
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation respon were observed			
4,5-dichloro-2-octyl-2H-isothiaz	ol-3-one [DCOIT] (64359-8	1-5)				
Method	Species	Exposure route	Results			
OECD Test No. 406: Skin Sensitisation	Guinea pig	•	sensitising			
Germ cell mutagenicity	Based on available	data, the classification criteria	are not met.			
Carcinogenicity	Based on available o	data, the classification criteria	are not met.			
Reproductive toxicity	Based on available of	data, the classification criteria	are not met.			
	cal name		European Union			
Octamethylcyclo	otetrasiloxane [D4]		Repr. 2			
STOT - single exposure STOT - repeated exposure		data, the classification criteria data, the classification criteria				
Aspiration hazard	Based on available	data, the classification criteria	are not met.			
11.2. Information on other ha	azards					
11.2.1. Endocrine disrupting	g properties					
Endocrine disrupting proper	ties No information avail	able.				
11.2.2. Other information						
Other adverse effects	No information avail	able.				
SECTION 12: Ecologica	I information					
12.1. Toxicity						
Ecotoxicity	Harmful to aquatic li	fe with long lasting effects.				
-	e/aquatic Fish	Toxicity to Crustace	a M-Factor M-Fac			

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons,	EL50 (72h)	LL50 (96h) >	-	LL50 (48h)>		
C15-C20, n-alkanes,	>10,000 mg/L	1028 mg/L		3193 mg/l		
isoalkanes, cyclics, <	(Skeletonema	(Scophthalmus		(Acartia tonsa)		
0.03% aromatics	costatum)	maximus)				
RR-100252-4	ISO 10253	OECD 203				
Silica, amorphous	EC50: =440mg/L	LC50:	-	EC50:		

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

7631-86-9	(72h,	=5000mg/L (96h,		=7600mg/L (48h,		
	Pseudokirchneri	Brachydanio		Ceriodaphnia		
	ella subcapitata)	rerio)		dubia)		
Triacetoxy(propyl)silane	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
17865-07-5	approx. 24	108.89 mg/L		89.59 mg/L		
	mg/I(Pseudokirc			-		
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h) >500	-	EC50 (48h) >500		
triacetate	>500 mg/l	mg/l		mg/l (Daphnia		
4253-34-3	(Pseudokirchner	(Brachydanio		magna)		
	ella subcapitata)	rerio)				
Octamethylcyclotetrasil	-	LC50:	-	EC50:		10
oxane [D4]		>1000mg/L (96h,		=25.2mg/L (24h,		
556-67-2		Lepomis		Daphnia magna)		
		macrochirus)				
		LC50: >500mg/L				
		(96h,				
		Brachydanio				
		rerio)				
4,5-dichloro-2-octyl-2H-	EC50 (72h)	LC50 (96h)	-	EC50 (48h)	100	100
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus	mykiss)(OECD		(OECD 202)		
	subspicatus)(OE	203)				
	CD 201)					
Dimethylbis[(1-oxoneod	-	-	-	EC50 =39 mg/L		
ecyl)oxy]stannane				(Daphnia		
68928-76-7				magna)		
				(OECD 201)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Silica, amorphous (7631-86-9)

Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic
			substances

Octamethylcyclotetrasiloxane [D4] (556-67-2)

4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)

Method	Exposure time	Value	Results	
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days	
Anaerobic Transformation in Aquatic			-	
Sediment Systems				

Dimethylbis[(1-oxoneodecyl)oxy]stannane (68928-76-7)

Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	0%	Not readily biodegradable
Biodegradability: CO2 Evolution Test			
(TG 301 B)			
OECD Test No. 301F: Ready	28 days	3%	Not readily biodegradable
Biodegradability: Manometric	-		
Respirometry Test (TG 301 F)			

12.3. Bioaccumulative potential

Bioaccumulation

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

Component Information

Chemical name	Partition coefficient
Triacetoxy(propyl)silane	1.23
Silanetriol, methyl-, triacetate	-2.4
Octamethylcyclotetrasiloxane [D4]	6.49
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	4.4

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03%	The substance is not PBT / vPvB	
aromatics		
Silica, amorphous	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Triacetoxy(propyl)silane	The substance is not PBT / vPvB	
Silanetriol, methyl-, triacetate	The substance is not PBT / vPvB	
Octamethylcyclotetrasiloxane [D4]	PBT & vPvB	
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

Component Information			
Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Method Results Species			
Endocrine disrupting properties in accordance	Negative.		
with the criteria set out in Commission			
Delegated Regulation (EU) 2017/2100(3) or			
Commission Regulation (EU) 2018/605(4).			

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022 Revision date 07-Jun-2022 Revision Number 1

SECTION 14: Transport information

Land transport (ADR/RID) 14.1 UN number or ID number 14.2 Proper Shipping Name 14.3 Transport hazard class(es) 14.4 Packing group 14.5 Environmental hazards 14.6 Special Provisions	Not regulated Not regulated Not regulated Not regulated Not applicable None
IMDG	
14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk	Not applicable
according to IMO instruments	

Air trans	port (ICAO-TI / IATA-DGR)	
444 1111		ID	

14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Environmental hazards	Not applicable	
14.6 Special Provisions	None	

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 4,5-dichloro-2-octyl-2H-isothiazol-3-one

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

[DCOIT]

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Silica, amorphous	RG 25
7631-86-9	

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens	
Octamethylcyclotetrasiloxane [D4]	Fertility (Category 2)	
556-67-2		

DenmarkRegistration number(s) (P-no.)No information availableNorwayRegistration number(s) (PRN-no.)No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH014 - Reacts violently with water

EUH071 - Corrosive to the respiratory tract

H226 - Flammable liquid and vapour

```
H302 - Harmful if swallowed
```

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

ZWALUW SILICONE-1001U BROWN

Supercedes Date: 07-Jun-2022

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects H412 - Harmful to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB: Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWĂ	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	On basis of test data
Serious eye damage/eye irritation	On basis of test data
Respiratory sensitisation	Calculation method
Skin sensitisation	On basis of test data
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA) European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC) European Chemicals Agency (ECHA) (ECHA_API) EPA (Environmental Protection Agency) Acute Exposure Guideline Level(s) (AEGL(s)) International Uniform Chemical Information Database (IUCLID) National Institute of Technology and Evaluation (NITE) NIOSH (National Institute for Occupational Safety and Health) Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme Organisation for Economic Co-operation and Development Screening Information Data Set

ZWALUW SILICONE-1001U BROWN Supercedes Date: 07-Jun-2022

Prepared By	Product Safety & Regulatory Affairs
Revision date	07-Jun-2022
Training Advice	No information available
Further information	No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet