

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX Premium Building Silicone Black

Date: 28.03.2022

Replaces: 0075.16.BB **Ref:** 0436.0.BB/DL

1101: 0-00.0.DD/DD

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name SX Premium Building Silicone Black

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
Dodworth Business Park
Dodworth
Barnsley S75 3SP

Tel: 01226 771600 Fax: 01226 771601

www.siroflex.co.uk info.siroflex@bostik.com

1.4. Emergency telephone number

United Kingdom Ireland +44 (0) 1226 771600 (Office Hours Only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)

2.2. Label Elements

Contains: 2-Butanone, oxime & 3-(TriethoxysilyI) propylamine



Signal word Warning

Hazard statements

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H351 - Suspected of causing cancer.

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P405 - Store locked up.

P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other Hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
2-Butanone, oxime	202-496-6	96-29-7	1- <2.5	Acute Tox. 4 (H312) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 2 (H351)		01-2119539477- 28-XXXX
3-(Triethoxysilyl) propylamine	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 4 (H302)		01-2119480479- 24-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

General advice IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to

the doctor in attendance.

Remove to fresh air. Inhalation

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

> Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

Replaces: 0075.16.BB

persists.

Skin contact Wash with soap and water. May cause an allergic skin reaction. In the case of skin

irritation or allergic reactions see a doctor.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

4.2. Most important symptoms and effects, both acute and delayed

Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. **Symptoms**

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the Suitable extinguishing media

surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from

and upwind of spill/leak. Avoid contact with skin, eyes or clothing. Use personal

protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into

soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment

Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment. Take off contaminated clothing and wash it before reuse. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin,

eyes or clothing. Do not eat, drink or smoke when using this product.

General hygiene considerations Wash hands before breaks and immediately after handling the product. Avoid contact

with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat,

drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep out of the reach of children. Keep containers tightly closed in a

dry, cool and well-ventilated place. Protect from moisture.

7.3. Specific end use(s)

Specific Use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon

curing

Chemical name	European Union	Ireland	United Kingdom
Ethanol	-	STEL: 1000 ppm	TWA: 1000 ppm
64-17-5			TWA: 1920 mg/m ³
			STEL: 3000 ppm
			STEL: 5760 mg/m ³
2-Butanone, oxime	-	TWA: 3 ppm	-
96-29-7		TWA: 10 mg/m ³	
		STEL: 10 ppm	
		STEL: 33 mg/m ³	

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
3-(Triethoxysilyl) propylamine (919-30-2)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker Long term Systemic health effects	Inhalation	59 mg/m³			
worker Short term Systemic health effects	Inhalation	59 mg/m³			
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d			
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d			

Derived No Effect Level (DNEL)					
3-(Triethoxysilyl) propylamine (919-30-2)					
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	17 mg/m³			
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m³			
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d			
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC	
3-(Triethoxysilyl) propylamine (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Appearance Paste

Colour See section 1 for more information

Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
Evaporation rate
Flammability (solid, gas)
No data available
No data available
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data availableRelative densityNo data available

Water solubility Product cures with moisture

Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity $> 21 \text{ mm}^2/\text{s}$ **Dynamic viscosity** No data available **Explosive properties** No data available **Oxidising properties** No data available

9.2. Other information

Solid content (%)

VOC Content (%)

No information available
No information available

Density 1.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

SX Premium Building Silicone Black
Date: 28.03.2022

Date: 28.03.2022 Ref: 0436.0.BB/DL

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon

curing.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause

allergic reactions with susceptible persons. (based on components). Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may

cause redness and irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 77,500.00 mg/kg **ATEmix (dermal)** 64,035.30 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, oxime	=930 mg/kg (Rattus)	1000 - 1800 mg/kg	>4.83 mg/L (Rattus) 4 h
96-29-7		(Oryctolagus cuniculus)	•
3-(Triethoxysilyl) propylamine	LD50 = 1490 mg/kg (Rat,	LD50 = 4076 mg/kg	LC50 >144 mg/L (6h) Rat
919-30-2	female) EPA OTS 798.1175	(Oryctolagus cuniculus) EPA	(Vapour)
		OTS 798.1100	•

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients.

Chemical name	European Union
2-Butanone, oxime	Carc. 2
96-29-7	

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity .

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
2-Butanone, oxime	EC50: =83mg/L	LC50:	EC50 = 281	EC50:		
96-29-7	(72h,	=760mg/L (96h,	mg/L 17 h	=750mg/L (48h,		
	Desmodesmus	Poecilia	EC50 = 950	Daphnia magna)		
	subspicatus)	reticulata) LC50:	mg/L 5 min			
		777 - 914mg/L				
		(96h,				
		Pimephales				
		promelas) LC50:				
		320 - 1000mg/L				
		(96h, Leuciscus				
		idus)				
3-(Triethoxysilyl)	EC50 (72h)	LC50 (96h)	-	EC50 (48h)		
propylamine	>1000 mg/L	>934 mg/L		=331 mg/L		
919-30-2	Green algae	(Brachydanio		Daphnia magna		
	(desmodesmus	rerio) (OECD		(OECD TG 202)		
	subspicatus)	TG 203)				
	(OECD TG 201)					

SX Premium Building Silicone Black

Ref: 0436.0.BB/DL

12.2. Persistence and degradability

No information available. Persistence and degradability

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Date: 28.03.2022

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
2-Butanone, oxime 96-29-7	0.65	5.8
3-(Triethoxysilyl) propylamine 919-30-2	1.7	3.4

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
2-Butanone, oxime 96-29-7	The substance is not PBT / vPvB
3-(Triethoxysilyl) propylamine 919-30-2	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated Not regulated 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Not regulated 14.4 Packing group Not regulated

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

14.5 Environmental hazards Not applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated

14.5 Marine pollutant NP14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

SX Premium Building Silicone Black

Date: 28.03.2022 Ref: 0436.0.BB/DL

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H351 - Suspected of causing cancer

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 14-Dec-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet