

Replaces: 0075.14.DBS

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX Premium Building Silicone Bronze

Date: 28.03.2022 Ref: 0522.0.BB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX Premium Building Silicone Bronze

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited Dodworth Business Park

Dodworth, Barnsley

South Yorkshire S75 3SP

Tel: 01226 771600 Fax: 01226 771601

www.siroflex.co.uk technical.siroflex@bostik.com **E-mail address** info.siroflex@bostik.com

1.4. Emergency telephone number

United Kingdom

+44 (0) 1226 771600 (Office Hours Only)

Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1A - (H317)
Carcinogenicity	Category 1B - (H350)
Specific target organ toxicity — single exposure	Category 2 - (H371)
Chronic aquatic toxicity	Category 3 - (H412)

2.2. Label elements

Contains 2-octyl-2H-isothiazol-3-one [OIT] & 2-Butanone, oxime & 3-(Triethoxysilyl) propylamine





Signal word Danger

Hazard statements

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H350 - May cause cancer.

United Kingdom - BE Page 1 / 15

SX Premium Building Silicone Bronze

Date: 28.03.2022 Ref: 0522.0.BB/DL

Replaces: 0075.14.DBS

H371 - May cause damage to organs.

H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P201 - Obtain special instructions before use

P260 - Do not breathe dust/fume/gas/mist/vapours/spray

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P308 + P311 - IF exposed or concerned: Call a POISON CENTER or doctor

P362 + P364 - Take off contaminated clothing and wash it before reuse

P501 - Dispose of contents/ container to an approved waste disposal plant

Special provisions concerning the labelling of certain mixtures

Restricted to professional users.

2.3. Other hazards

Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing. Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing. Causes mild skin irritation. Harmful to aquatic life.

PRT & vPvB

This mixture contains substances considered to be persistent, bio-accumulating and toxic (PBT). This mixture contains substances considered to be very persistent and very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
2-Butanone, oxime	202-496-6	96-29-7	1- <2.5	Acute Tox. 3 (H301) Acute Tox. 4 (H312) Skin Irrit. 2 (H315) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 1B (H350) STOT SE 3 (H336) STOT SE 1 (H370) STOT RE 2 (H373)		01-2119539477- 28-XXXX
3-(Triethoxysilyl) propylamine	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Acute Tox. 4 (H302)		01-2119480479- 24-XXXX

United Kingdom - BE Page 2/15

SX Premium Building Silicone Bronze

Date: 28.03.2022

Ref: 0522.0.BB/DL

		1		Г		Т
Titanium dioxide	236-675-5	13463-67-7	0.1 - <1	Carc. 2 (H351i)		01-2119489379- 17-XXXX
Silica, amorphous	231-545-4	7631-86-9	0.1 - <1	-		01-2119379499- 16-XXXX
Octamethylcyclotetrasilo xane [D4]	209-136-7	556-67-2	0.01 - <0.1	Repr. 2 (H361f) Aquatic Chronic 1 (H410) Flam. Liq. 3 (H226) (M Factor Chronic = 10) PBT vPBT		01-2119529238- 36-XXXX
2-octyl-2H-isothiazol-3-o ne [OIT]	247-761-7	26530-20-1	0.0015 - <0.01	Acute Tox. 3 (H301) Acute Tox. 3 (H311) Acute Tox. 2 (H330) Skin Corr. 1B (H314) Eye Dam 1 (H318) Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410) M Factor Acute =100 M Factor Chronic = 100	Skin Sens. 1A :: C>=0.0015%	-

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. Consult an ophthalmologist.

Skin contact Wash with soap and water. May cause an allergic skin reaction. Wash off immediately

with plenty of water for at least 15 minutes. If symptoms persist, call a doctor.

Ingestion Never give anything by mouth to an unconscious person. Rinse mouth thoroughly with

water. Drink 1 or 2 glasses of water. Do NOT induce vomiting.

United Kingdom - BE Page 3 / 15

SX Premium Building Silicone Bronze

Self-protection of the first aider

Date: 28.03.2022 Ref: 0522.0.BB/DL

Replaces: 0075.14.DBS

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

Hazardous combustion products Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon oxides. Silicon dioxide. Thermal

decomposition can lead to release of irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautionsDo not get in eyes, on skin, or on clothing. Use personal protective equipment as

required. Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containmentDo not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

United Kingdom - BE Page 4 / 15

SX Premium Building Silicone Bronze

7.1. Precautions for safe handling

Date: 28.03.2022

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. Avoid breathing vapours or

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

mists.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	United Kingdom
Ethanol	-	TWA: 1000 ppm
64-17-5		TWA: 1920 mg/m ³
		STEL: 3000 ppm
		STEL: 5760 mg/m ³
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Silica, amorphous	TWA: 0.1 mg/m ³	TWA: 6 mg/m ³
7631-86-9		TWA: 2.4 mg/m ³
		TWA: 0.1 mg/m ³
		STEL: 18 mg/m ³
		STEL: 7.2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
2-Butanone, oxime (96-29-7)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
DNEL/DMEL Long term Systemic health effects	Inhalation	0.028 mg/m³	
Long term Local health effects	Inhalation	0.9 mg/m³	
DNEL/DMEL	Dermal	0.004 mg/kg bw/d	

United Kingdom - BE Page 5 / 15

SX Premium Building Silicone Bronze
Date: 28.03.2022

Replaces: 0075.14.DBS
Ref: 0522.0.BB/DL

Long term Systemic health effects			
3-(Triethoxysilyl) propylamin	ne (919-30-2)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m³	
worker Short term Systemic health effects	Inhalation	59 mg/m³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	
Titanium dioxide (13463-67-7	7)		
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m³	
Ostomothylovolototrocilovon	o ID41 (FEC 67.2)		
Octamethylcyclotetrasiloxan Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	73 mg/m³	
	1	1	1
Derived No Effect Level (DNI 2-Butanone, oxime (96-29-7)	EL)		
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	0.00482 mg/m³	
Long term Local health effects	Dermal	0.43 mg/m³	
3-(Triethoxysilyl) propylamin	ne (919-30-2)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m³	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m³	
Consumer	Dermal	5 mg/kg bw/d	
Long term Systemic health effects			

Titanium dioxide (13463-67-7)

United Kingdom - BE Page 6 / 15

SX Premium Building Silicone Bronze

Date: 28.03.2022

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

Туре		Derived No Effect Level (DNEL)	Safety factor
Consumer	Oral	700 mg/kg bw/d	
Long term			
Systemic health effects			

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
Туре	Exposure route	Derived No Effect Level	Safety factor	
		(DNEL)		
Consumer	Inhalation	13 mg/m ³		
Long term				
Systemic health effects				
Consumer	Oral	3.7 mg/kg bw/d		
Long term				
Systemic health effects				

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
3-(Triethoxysilyl) propylamine (919-30-2)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.33 mg/l		
Marine water	0.033 mg/l		

Titanium dioxide (13463-67-7)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Marine water	0.0184 mg/l		
Freshwater sediment	1000 mg/kg		
Freshwater	0.184 mg/l		
Marine sediment	100 mg/kg		
Soil	100 mg/kg		
Microorganisms in sewage treatment	100 mg/l		
Freshwater - intermittent	0.193 mg/l		

Octamethylcyclotetrasiloxane [D4] (556-67-2)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	0.0015 mg/l		
Marine water	0.00015 mg/l		
Freshwater sediment	3 mg/kg		
Marine sediment	0.3 mg/kg		
Soil	0.54 mg/kg		
Sewage treatment plant	10 mg/l		

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

United Kingdom - BE Page 7 / 15

SX Premium Building Silicone Bronze

Date: 28.03.2022

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Appearance Paste

Colour See section 1 for more information

Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

pH No data available Not applicable Insoluble in water

pH (as aqueous solution)
Melting point / freezing point
Initial boiling point and boiling

No data available
No data available

range

Flash point

Evaporation rate
Flammability

No data available
No data available
No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data availableRelative densityNo data available

Water solubility Product cures with moisture

Solubility(ies) No data available **Partition coefficient** No data available **Autoignition temperature** No data available **Decomposition temperature** No data available $> 21 \text{ mm}^2/\text{s}$ Kinematic viscosity Dynamic viscosity No data available **Explosive properties** No data available No data available Oxidising properties

9.2. Other information

Solid content (%) No information available

VOC Content (%)

Density 1.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

United Kingdom - BE Page 8 / 15

SX Premium Building Silicone Bronze

Date: 28.03.2022 Ref: 0522.0.BB/DL

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture. Exposure to air or moisture over

prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and

Replaces: 0075.14.DBS

sources of ignition.

10.5. Incompatible materials

Strong oxidising agents. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition

products

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. May cause drowsiness or dizziness.

Specific test data for the substance or mixture is not available. Causes serious eye Eye contact

irritation. (based on components). May cause redness, itching, and pain.

May cause sensitisation by skin contact. Specific test data for the substance or mixture Skin contact

> is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact

may cause redness and irritation. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high

vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and irritation.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

8,333.30 mg/kg ATEmix (oral) ATEmix (dermal) 64,642.00 mg/kg

Component Information

United Kingdom - BE Page 9/15

SX Premium Building Silicone Bronze

Date: 28.03.2022

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, oxime 96-29-7	=100 mg/kg (ATE)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
3-(Triethoxysilyl) propylamine 919-30-2	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175 LD50 = 2690 mg/kg (Rat, male) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
Silica, amorphous 7631-86-9	=7900 mg/kg (Rattus)	> 5000 mg/kg (Oryctolagus cuniculus)	>2.2 mg/L (Rattus) 1 h
Octamethylcyclotetrasiloxane [D4] 556-67-2	LD50 > 4800 mg/kg (Rattus) OECD 401	LD50 > 2400 mg/kg (Rattus) OECD 402	=36 g/m³ (Rattus) 4 h
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	=125 mg/kg (Rattus)	= 690 mg/kg (Oryctolagus cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation. Classification based on data available for ingredients.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Contains a known or suspected carcinogen. Classification based on data available for Carcinogenicity ingredients. May cause cancer.

Chemical name	European Union
2-Butanone, oxime 96-29-7	Carc. 1B
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Based on available data, the classification criteria are not met. Reproductive toxicity

Chemical name	European Union
Octamethylcyclotetrasiloxane [D4]	Repr. 2
556-67-2	·

STOT - single exposure Based on the classification criteria of the Globally Harmonized System as adopted in the

country or region with which this safety data sheet complies, this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE).

May cause damage to organs. May cause drowsiness or dizziness.

H371 - May cause damage to the following organs: upper respiratory tract.

Based on available data, the classification criteria are not met. STOT - repeated exposure

United Kingdom - BE Page 10/15

SX Premium Building Silicone Bronze

Date: 28.03.2022 Ref: 0522.0.BB/DL

Aspiration hazard

Based on available data, the classification criteria are not met.

Replaces: 0075.14.DBS

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms		M-Factor	M-Factor (long-term)
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, Desmodesmus subspicatus)	LC50: =760mg/L (96h, Poecilia reticulata) LC50: 777 - 914mg/L (96h, Pimephales promelas) LC50: 320 - 1000mg/L (96h, Leuciscus idus)	mg/L 5 min	EC50: =750mg/L (48h, Daphnia magna)		
3-(Triethoxysilyl) propylamine 919-30-2	EC50 (72h) >1000 mg/L Green algae (desmodesmus subspicatus) (OECD TG 201)	LC50 (96h) >934 mg/L (Brachydanio rerio) (OECD TG 203)	-	EC50 (48h) =331 mg/L Daphnia magna (OECD TG 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Silica, amorphous 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneri ella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)		
Octamethylcyclotetrasil oxane [D4] 556-67-2	<u>-</u>	LC50: >1000mg/L (96h, Lepomis macrochirus) LC50: >500mg/L (96h, Brachydanio rerio)	-	EC50: =25.2mg/L (24h, Daphnia magna)		10
2-octyl-2H-isothiazol-3- one [OIT] 26530-20-1	EC50(72h) = 0.084 mg/L (Scenedesmus	LC50 (96h) = 0.036 mg/L (Oncorhynchus	-	EC50 (48h) =0.42 mg/L (OECD 202)	100	100

United Kingdom - BE Page 11 / 15

SX Premium Building Silicone Bronze Date: 28.03.2022

Date: 28.03.2022 Ref: 0522.0.BB/DL

Replaces: 0075.14.DBS

subspicatus)	mykiss) (OECD		
(OECD 201)	203)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Informatio	n		
Silica, amorphous (763	1-86-9)		
Method	Exposure time	Value	Results
			The methods for determining biodegradability are not applicable to inorganic substances

Octamethylcyclotetrasiloxane [D4] (556-67-2)				
2-octyl-2H-isothiazol-3-one [OIT] (26530-20-1)				
Method	Exposure time	Value	Results	
OECD Test No. 309: Aerobic		Half-life 0.6-1.4 d	Readily biodegradable	
Mineralization in Surface Water -				
Simulation Biodegradation Test				

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
2-Butanone, oxime 96-29-7	0.65	5.8
3-(Triethoxysilyl) propylamine 919-30-2	1.7	3.4
Octamethylcyclotetrasiloxane [D4] 556-67-2	6.49	12400
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	2.92	-

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
2-Butanone, oxime 96-29-7	The substance is not PBT / vPvB
3-(Triethoxysilyl) propylamine 919-30-2	The substance is not PBT / vPvB
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
Silica, amorphous 7631-86-9	The substance is not PBT / vPvB PBT assessment does not apply
Octamethylcyclotetrasiloxane [D4] 556-67-2	PBT & vPvB
2-octyl-2H-isothiazol-3-one [OIT] 26530-20-1	The substance is not PBT / vPvB

United Kingdom - BE Page 12 / 15

SX Premium Building Silicone Bronze

Date: 28.03.2022 Ref: 0522.0.BB/DL

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

regulations as applicable.

Contaminated packaging

Handle contaminated packages in the same way as the product itself.

European Waste Catalogue

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

Replaces: 0075.14.DBS

substances

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
44 E Marina nallutant	ND

14.5 Marine pollutant NP **14.6 Special Provisions** None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

United Kingdom - BE Page 13/15

SX Premium Building Silicone Bronze

Date: 28.03.2022

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Biocidal Products Regulation (EU) No 528/2012 (BPR)

This product contains a biocidal product for the preservation of the dry film Contains: 2-octyl-2H-isothiazol-3-one [OIT]

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H301 - Toxic if swallowed

H302 - Harmful if swallowed

H311 - Toxic in contact with skin

H312 - Harmful in contact with skin

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H336 - May cause drowsiness or dizziness

H350 - May cause cancer

H351i - Suspected of causing cancer if inhaled

H361f - Suspected of damaging fertility

United Kingdom - BE Page 14/15

SX Premium Building Silicone Bronze

Replaces: 0075.14.DBS

Ref: 0522.0.BB/DL

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

H400 - Very toxic to aquatic life

Date: 28.03.2022

H410 - Very toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 21-Dec-2021

Indication of changes

Revision note SDS sections updated, 2, 3.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 15/15