

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name SX PREMIUM BUILDING SILICONE (CLEAR)
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Siroflex Limited
 Dodworth Business Park
 Dodworth
 Barnsley
 S75 3SP
 Tel: 01226 771600 Fax: 01226 771601

1.4. Emergency telephone number

United Kingdom +44 (0)1226 771600 (Office Hours Only)
Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)

2.2. Label Elements

Contains: 2-Butanone, oxime & 3-(Triethoxysilyl) propylamine



Signal word
 Warning

Hazard statements

H317 - May cause an allergic skin reaction.
 H319 - Causes serious eye irritation.
 H351 - Suspected of causing cancer.

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P264 - Wash face, hands and any exposed skin thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P405 - Store locked up.
P501 - Dispose of contents/ container to an approved waste disposal plant.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other Hazards

Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing
Small amounts of 2-butanone, oxime (CAS 96-29-7) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
2-Butanone, oxime	202-496-6	96-29-7	1- <2.5	Acute Tox. 4 (H312) Eye Dam. 1 (H318) Skin Sens. 1 (H317) Carc. 2 (H351)		01-2119539477-28-XXXX
3-(Triethoxysilyl) propylamine	213-048-4	919-30-2	0.1 - <1	Skin Corr. 1B (H314) Skin Sens. 1 (H317) Acute Tox. 4 (H302)		01-2119480479-24-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash with soap and water. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.
Self-protection of the first aider	Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section 8).

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical Product is or contains a sensitiser. May cause sensitisation by skin contact.

Hazardous combustion products Carbon dioxide (CO₂). Nitrogen oxides (NO_x). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

Environmental precautions Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Take off contaminated clothing and wash it before reuse. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

General hygiene considerations Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep out of the reach of children. Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from moisture.

7.3. Specific end use(s)

Specific Use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing

Chemical name	European Union	Ireland	United Kingdom
Ethanol 64-17-5	-	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1920 mg/m ³ STEL: 3000 ppm STEL: 5760 mg/m ³
2-Butanone, oxime 96-29-7	-	TWA: 3 ppm TWA: 10 mg/m ³ STEL: 10 ppm STEL: 33 mg/m ³	-

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
3-(Triethoxysilyl) propylamine (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	59 mg/m ³	
worker Short term Systemic health effects	Inhalation	59 mg/m ³	
worker Long term Systemic health effects	Dermal	8.3 mg/kg bw/d	
worker Short term Systemic health effects	Dermal	8.3 mg/kg bw/d	

Derived No Effect Level (DNEL)			
3-(Triethoxysilyl) propylamine (919-30-2)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	17.4 mg/m ³	
Consumer Long term Systemic health effects	Dermal	5 mg/kg bw/d	
Consumer Short term Systemic health effects	Dermal	5 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
3-(Triethoxysilyl) propylamine (919-30-2)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Marine water	0.033 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166

Hand protection

Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection

None under normal use conditions.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

Recommended filter type: especially in confined areas.
Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	See section 1 for more information
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	No data available	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	Product cures with moisture	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	> 21 mm ² /s	
Dynamic viscosity	No data available	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	No information available
Density	1.02

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	None.

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products Small amounts of ethanol (CAS 64-17-5) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitisation by skin contact. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	77,500.00 mg/kg
ATEmix (dermal)	64,035.30 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
2-Butanone, oxime 96-29-7	=930 mg/kg (Rattus)	1000 - 1800 mg/kg (Oryctolagus cuniculus)	>4.83 mg/L (Rattus) 4 h
3-(Triethoxysilyl) propylamine 919-30-2	LD50 = 1490 mg/kg (Rat, female) EPA OTS 798.1175	LD50 = 4076 mg/kg (Oryctolagus cuniculus) EPA OTS 798.1100	LC50 >144 mg/L (6h) Rat (Vapour)

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation May cause skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitisation May cause sensitisation by skin contact.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients.

Chemical name	European Union
2-Butanone, oxime 96-29-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
2-Butanone, oxime 96-29-7	EC50: =83mg/L (72h, <i>Desmodesmus subspicatus</i>)	LC50: =760mg/L (96h, <i>Poecilia reticulata</i>) LC50: 777 - 914mg/L (96h, <i>Pimephales promelas</i>) LC50: 320 - 1000mg/L (96h, <i>Leuciscus idus</i>)	EC50 = 281 mg/L 17 h EC50 = 950 mg/L 5 min	EC50: =750mg/L (48h, <i>Daphnia magna</i>)		
3-(Triethoxysilyl) propylamine 919-30-2	EC50 (72h) >1000 mg/L Green algae (<i>desmodesmus subspicatus</i>) (OECD TG 201)	LC50 (96h) >934 mg/L (<i>Brachydanio rerio</i>) (OECD TG 203)	-	EC50 (48h) =331 mg/L <i>Daphnia magna</i> (OECD TG 202)		

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
2-Butanone, oxime 96-29-7	0.65	5.8
3-(Triethoxysilyl) propylamine 919-30-2	1.7	3.4

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment .

Chemical name	PBT and vPvB assessment
2-Butanone, oxime 96-29-7	The substance is not PBT / vPvB
3-(Triethoxysilyl) propylamine 919-30-2	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 09* waste adhesives and sealants containing organic solvents or other dangerous substances

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

14.5 Environmental hazards Not applicable
14.6 Special Provisions None

IMDG

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Marine pollutant NP
14.6 Special Provisions None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number Not regulated
14.2 Proper Shipping Name Not regulated
14.3 Transport hazard class(es) Not regulated
14.4 Packing group Not regulated
14.5 Environmental hazards Not applicable
14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

SAFETY DATA SHEET

SX Premium Building Silicone Clear
Date: 28.03.2022

Replaces: 0075.16.BB
Ref: 0438.0.BB/DL

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H302 - Harmful if swallowed
H312 - Harmful in contact with skin
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H318 - Causes serious eye damage
H351 - Suspected of causing cancer

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 14-Dec-2020

Indication of changes

Revision note Not applicable.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet