



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name SX POLYFLEX HM BLACK
Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against Consumer use

1.3. Details of the supplier of the safety data sheet

Company Name
Siroflex Limited
Dodworth Business Park
Dodworth, Barnsley
South Yorkshire, S75 3SP
Tel: 01226 771600 Fax: 01226 771601
www.siroflex@bostik.com technical.siroflex@bostik.com

E-mail address info.siroflex@bostik.com

1.4. Emergency telephone number

United Kingdom 01226 771600 (Office Hours Only)
Ireland

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction
EUH204 - Contains isocyanates. May produce an allergic reaction
EUH210 - Safety data sheet available on request

Special provisions concerning the labelling of certain mixtures

Reserved for industrial and professional use. As from 24 August 2023 adequate training is required before industrial or professional use.

2.3. Other hazards

Causes mild skin irritation.

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Xylene (reaction mass of ethylbenzene and xylene)	905-588-0	RR-45541-4	5 - <10	STOT SE 3 (H335) STOT RE 2 (H373) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Acute Tox. 4 (H312) Acute Tox. 4 (H332) Flam Liq. 3 (H226) Aquatic Chronic 3 (H412)	STOT RE 2 (H373):: C>=10%	01-2119488216-32-xxxx
Carbon black	215-609-9	1333-86-4	1- <2.5	^		01-2119384822-32-XXXX
Aromatic Polyisocyanate	-	53317-61-6	0.1 - <1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)		[7]
Ethyl acetate	205-500-4	141-78-6	0.1 - <1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119475103-46-XXXX
4,4'-Methylenediphenyl diisocyanate	202-966-0	101-68-8	0.01 - <0.1	Acute Tox. 4 (H332) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	01-2119457014-47-XXXX

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

				STOT SE 3 (H335) STOT RE 2 (H373)		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.01 - <0.1	Skin Sens. 1A (H317) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119491304-40-XXXX
m-tolylidene diisocyanate	247-722-4	26471-62-5	0.01 - <0.1	Acute Tox. 1 (H330) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) STOT SE 3 (H335) Aquatic Chronic 3 (H412)	Resp. Sens. 1 :: C>=0.1%	01-2119454791-34-XXXX

NOTE [5] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex V of REACH

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
Ingestion	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Prolonged contact may cause redness and irritation.
-----------------	---

4.3. Indication of any immediate medical attention and special treatment needed

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Note to doctors Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical No information available.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO₂). Hydrocarbons. Nitrogen oxides (NO_x). Aldehydes. Hydrochloric Acid. Sulphur oxides.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Do not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture.

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Recommended storage temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)
Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Polyvinyl chloride 9002-86-2	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Limestone 1317-65-3	-	TWA: 10 mg/m ³ TWA: 4 mg/m ³ STEL: 30 mg/m ³ STEL: 12 mg/m ³
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	TWA: 50 ppm TWA: 221 mg/m ³ STEL: 100 ppm STEL: 442 mg/m ³ S*	STEL: 100 ppm STEL: 441 mg/m ³ TWA: 50 ppm TWA: 220 mg/m ³ Skin
Carbon black 1333-86-4	-	TWA: 3.5 mg/m ³ STEL: 7 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	221 mg/m ³	
worker Long term Local health effects	Inhalation	221 mg/m ³	
worker Short term Local health effects	Inhalation	442 mg/m ³	
worker Long term Systemic health effects	Dermal	212 mg/kg bw/d	
Carbon black (1333-86-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term	Inhalation	2 mg/m ³	

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Systemic health effects			
worker	Inhalation	2 mg/m ³	
Long term			
Local health effects			

Ethyl acetate (141-78-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Dermal	63 mg/kg bw/d	
Long term			
Systemic health effects			
worker	Inhalation	1468 mg/m ³	
Short term			
Systemic health effects			
worker	Inhalation	734 mg/m ³	
Long term			
Local health effects			
worker	Inhalation	1468 mg/m ³	
Short term			
Local health effects			
worker	Inhalation	734 mg/m ³	
Long term			
Systemic health effects			

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Dermal	50 mg/kg bw/d	
Short term			
Systemic health effects			
worker	Inhalation	0.1 mg/m ³	
Short term			
Systemic health effects			
worker	Dermal	28700 µg/cm ²	
Short term			
Local health effects			
worker	Inhalation	0.1 mg/m ³	
Short term			
Local health effects			
worker	Inhalation	0.05 mg/m ³	
Long term			
Systemic health effects			
worker	Inhalation	0.05 mg/m ³	
Long term			
Local health effects			

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)			
m-tolylidene diisocyanate (26471-62-5)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	0.035 mg/m ³	
Long term			
Systemic health effects			
worker	Inhalation	0.14 mg/m ³	
Short term			
Systemic health effects			
worker	Inhalation	0.035 mg/m ³	
Long term			
Local health effects			

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

worker Short term Local health effects	Inhalation	0.14 mg/m ³	
--	------------	------------------------	--

Derived No Effect Level (DNEL)			
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	260 mg/m ³	
Consumer Long term Local health effects	Inhalation	65.3 mg/m ³	
Consumer Short term Local health effects	Inhalation	260 mg/m ³	
Consumer Long term Systemic health effects	Dermal	125 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	12.5 mg/kg bw/d	

Ethyl acetate (141-78-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m ³	
Consumer Long term Local health effects	Inhalation	367 mg/m ³	
Consumer Short term Local health effects	Inhalation	734 mg/m ³	
Consumer Long term Systemic health effects	Inhalation	367 mg/m ³	

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Short term Systemic health effects	Dermal	25 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	0.05 mg/m ³	
Consumer	Oral	20 mg/kg bw/d	

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Short term Systemic health effects			
Consumer Short term Local health effects	Dermal	17200 µg/cm²	
Consumer Short term Local health effects	Inhalation	0.05 mg/m³	
Consumer Long term Systemic health effects	Inhalation	0.025 mg/m³	
Consumer Long term Local health effects	Inhalation	0.025 mg/m³	

Predicted No Effect Concentration No information available.
(PNEC)

Predicted No Effect Concentration (PNEC)	
Xylene (reaction mass of ethylbenzene and xylene) (RR-45541-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.327 mg/l
Marine water	0.327 mg/l
Microorganisms in sewage treatment	6.58 mg/l
Freshwater sediment	12.46 mg/kg dry weight
Soil	2.31 mg/kg dry weight

Carbon black (1333-86-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	5 mg/l
Marine water	5 mg/l

Ethyl acetate (141-78-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.26 mg/l
Marine water	0.026 mg/l
Freshwater sediment	1.25 mg/kg
Marine sediment	0.125 mg/kg
Soil	0.24 mg/kg
Microorganisms in sewage treatment	650 mg/l

4,4'-Methylenediphenyl diisocyanate (101-68-8)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	1 mg/l
Marine water	0.1 mg/l
Soil	1 mg/kg dry weight
Sewage treatment plant	1 mg/l
Freshwater - intermittent	10 mg/l

m-tolylidene diisocyanate (26471-62-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.013 mg/l
Marine water	0.00125 mg/l
Microorganisms in sewage treatment	>1 mg/l
Soil	>1 mg/kg dry weight

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374
Skin and body protection	Suitable protective clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	Black
Odour	Characteristic
Odour threshold	No information available

Property	Values	Remarks • Method
pH	.	
pH (as aqueous solution)	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	Not applicable . °C	
Flash point	> 61 °C	
Evaporation rate	No data available	
Flammability	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	No data available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	600000 mm ² /s	
Dynamic viscosity	600000 mPa s	
Explosive properties	No data available	
Oxidising properties	No data available	

9.2. Other information

Solid content (%)	No information available
VOC Content (%)	
Density	1.23 g/cm ³

SECTION 10: Stability and reactivity

10.1. Reactivity

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Protect from moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information .

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Prolonged contact may cause redness and irritation.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 10,513.50 mg/kg

ATEmix (inhalation-vapour) 251.70 mg/l

Component Information

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	=3500 mg/kg (Rattus)	>10000 mg/kg (Oryctolagus cuniculus)	=>47635 mg/L (Rattus) 4 h = >5000 ppm (Rattus) 4 h
Carbon black 1333-86-4	LD50 > 8000 mg/kg (Rattus) OECD 401	> 3 g/kg (Oryctolagus cuniculus)	> 4.6 mg/m ³ (Rat) 4 h
Aromatic Polyisocyanate 53317-61-6	LD50 >2000 mg/Kg (Rattus)		LC50 >3.820 mg/L (Rattus) 4h dust/mist
Ethyl acetate 141-78-6	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
4,4'-Methylenediphenyl diisocyanate 101-68-8	=31600 mg/kg (Rattus) = 9200 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus) OECD 402	=1.5 mg/L (Rattus) 4 h
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	LD50 = 3230 mg/Kg (Rat) OECD 401	LD50 >3170 mg/Kg (Rat)	
m-tolylidene diisocyanate 26471-62-5	=3060 mg/kg (Rattus)	= 10000 mg/kg (Oryctolagus cuniculus)	=0.107 mg/L (Rattus) 4 h (Vapour)

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Chemical name	European Union
4,4'-Methylenediphenyl diisocyanate 101-68-8	Carc. 2
m-tolylidene diisocyanate 26471-62-5	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	EC50 (72hr) 2.2 mg/l (Selenastrum capricornutum)	LC50(96h) 2.6 mg/l (Oncorhynchus mykiss-OECD 203)	EC50 = 0.0084 mg/L 24 h	LC50(24h) 1 mg/l (Daphnia magna-OECD 202)		
Carbon black 1333-86-4	>10000 mg/l (Desmodesmus subspicatus) OECD 202	>1000 mg/l (Brachydanio rerio) OCDE 203	-	EC50: >5600mg/L (24h, Daphnia magna)		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales promelas)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		
4,4'-Methylenediphenyl diisocyanate 101-68-8	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	>1000 mg/l (Danio rerio)	-	EC50 (24H) >1000 mg/L Daphnia magna		
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	EC50 (72 h) 1,68 mg/l (growth rate), Desmodesmus subspicatus (OECD 201)	LC50 (96 h) 0,9 mg/l, Brachydanio rerio (OECD 203)	-	-	1	

12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information

Aromatic Polyisocyanate (53317-61-6)

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)		biodegradation	34 % Not readily biodegradable

4,4'-Methylenediphenyl diisocyanate (101-68-8)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	3.15	25.9
Carbon black 1333-86-4	-	99
Ethyl acetate 141-78-6	0.6	30
4,4'-Methylenediphenyl diisocyanate 101-68-8	4.51	200
m-tolylidene diisocyanate 26471-62-5	-	5

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Xylene (reaction mass of ethylbenzene and xylene) RR-45541-4	The substance is not PBT / vPvB
Carbon black 1333-86-4	The substance is not PBT / vPvB PBT assessment does not apply
Ethyl acetate 141-78-6	The substance is not PBT / vPvB PBT assessment does not apply
4,4'-Methylenediphenyl diisocyanate 101-68-8	The substance is not PBT / vPvB
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	The substance is not PBT / vPvB
m-tolylidene diisocyanate 26471-62-5	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects No information available.

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Do not reuse empty containers.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

74 If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking
H225 - Highly flammable liquid and vapour
H226 - Flammable liquid and vapour
H304 - May be fatal if swallowed and enters airways
H312 - Harmful in contact with skin
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H330 - Fatal if inhaled
H332 - Harmful if inhaled
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer
H361f - Suspected of damaging fertility
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure

SAFETY DATA SHEET

SX POLYFLEX HM BLACK
Date: 25.01.2022

Replaces: 0256.43.BF
Ref: 0493.0.BF/DL

EWC European Waste Catalogue

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Sep-2021

Indication of changes

Revision note Not applicable.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet