

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008 This SDS is for generic information purposes and does not reflect required country specific information for OEL

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Revision date 17-Mar-2021 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name	BOSTIK H750 SEALNBOND PREMIUM BLACK
Pure substance/mixture	Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Sealant.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company Name Bostik SA 420 rue d'Estienne d'Orves 92700 Colombes FRANCE Tel: +33 (0)1 49 00 90 00

E-mail address

SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone

No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word None

Hazard statements This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane. May produce an allergic reaction EUH210 - Safety data sheet available on request

2.3. Other hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. May be harmful in contact with skin. Causes mild skin irritation. Harmful to aquatic life.

PBT & vPvB

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <5	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215- 52-XXXX
1-Propanamine, 3-(trimethoxysilyl)-	237-511-5	13822-56-5	1 - <2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		01-2119510159- 45-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.	
Inhalation	Remove to fresh air. If symptoms persist, call a doctor.	
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
Skin contact	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.	
Ingestion	Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.	
4.2. Most important symptoms and	d effects, both acute and delayed	
Symptoms	None known.	

4.3. Indication of any immediate medical attention and special treatment needed

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Note to doctors	Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.			
SECTION 5: Firefighting mea	asures			
5.1. Extinguishing media				
Suitable Extinguishing Media	Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.			
Unsuitable extinguishing media	Full water jet.			
5.2. Special hazards arising from the	ne substance or mixture			
Specific hazards arising from the chemical	Thermal decomposition can lead to release of irritating gases and vapours.			
Hazardous combustion products	Carbon monoxide. Carbon dioxide (CO2). Hydrocarbons. Nitrogen oxides (NOx). Silicon oxides. Silicon dioxide.			
5.3. Advice for firefighters				
Special protective equipment and precautions for fire-fighters	Wear self contained breathing apparatus for fire fighting if necessary.			
SECTION 6: Accidental release measures				
6.1. Personal precautions, protecti	ve equipment and emergency procedures			
Personal precautions	Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.			
For emergency responders	Use personal protection recommended in Section 8.			
6.2. Environmental precautions				
Environmental precautions	Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.			
6.3. Methods and material for conta	ainment and cleaning up			
Methods for containment	Do not scatter spilled material with high pressure water streams.			
Methods for cleaning up	Take up mechanically, placing in appropriate containers for disposal.			
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.			
6.4. Reference to other sections				
Reference to other sections	See section 8 for more information. See section 13 for more information.			
SECTION 7: Handling and st	orage			
7.1. Precautions for safe handling	_			
Advice on safe handling	Ensure adequate ventilation.			

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

7.2. Conditions for safe storage, including any incompatibilities

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Storage Conditions

Protect from moisture. Keep away from food, drink and animal feedingstuffs.

7.3. Specific end use(s)

Specific use(s) Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union	
Methyl alcohol	TWA: 200 ppm	
67-56-1	TWA: 260 mg/m ³	
	*	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Trimethoxyvinylsilane (2768-02-	Trimethoxyvinylsilane (2768-02-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Inhalation	27,6 mg/m³	
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d	

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	58 mg/m³	
worker Long term	Dermal	8.3 mg/kg bw/d	
Short term worker	Inhalation	58 mg/m³	
Short term worker	Dermal	8.3 mg/kg bw/d	

Derived No Effect Level (DN	EL)		
Trimethoxyvinylsilane (2768	Trimethoxyvinylsilane (2768-02-7)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³	
Consumer Systemic health effects	Dermal	7,8 mg/kg bw/d	

BOSTIK H750 SEALNBOND PREMIUM BLACK

Revision date 17-Mar-2021 Revision Number 2

Supercedes Date: 17-Mar-2021

Long term			
Consumer Systemic health effects	Oral	0,3 mg/kg bw/d	
Long term			

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Microorganisms in sewage treatment	13 mg/l
Soil	0.04 mg/l
Marine water	0.033 mg/l

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
Hand protection	Wear suitable gloves. Recommended Use:. Neoprene [™] . Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
Skin and body protection	None under normal use conditions.
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Appearance Colour Odour Odour threshold	Solid Paste Black No information available No information available	
Property pH pH (as aqueous solution) Melting point / freezing point Initial boiling point and boiling range Flash point Evaporation rate Flammability	Values No data available No data available No data available No data available No data available No data available No data available	Remark

Remarks · Method

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Flammability Limit in Air			
Upper flammability or explosive	No data available		
limits			
Lower flammability or explosive	No data available		
limits			
Vapour pressure	No data available		
Relative vapour density	No data available		
Relative density	No data available		
Water solubility	No data available		
Solubility(ies)	No data available		
Partition coefficient	No data available		
Autoignition temperature	No data available		
Decomposition temperature	No data available		
Kinematic viscosity	No data available		
Dynamic viscosity	No data available		
Explosive properties	No data available		
Oxidising properties	No data available		
9.2. Other information			
Solid content (%)	No information available		
VOC Content (%)			
Density	1.45 - 1.51 g/cm ³		

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	Product cures with moisture.
10.2. Chemical stability	
Stability	Stable under normal conditions.
Explosion data	
Sensitivity to mechanical	None.
impact Sensitivity to static discharge	None.
10.3. Possibility of hazardous reac	tions
Possibility of hazardous reactions	None under normal processing.
10.4. Conditions to avoid	
Conditions to avoid	Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.
10.5. Incompatible materials	
Incompatible materials	None known based on information supplied.
10.6. Hazardous decomposition pro	oducts
Hazardous decomposition products	Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Information on likely routes of exposure				
Product Information				
Inhalation	Based on available data, the classification criteria are not met.			
Eye contact	Based on available data, the classification criteria are not met.			
Skin contact	Specific test data for the substance or mixture is not available. Causes mild skin irritation. May be harmful in contact with skin. May cause sensitisation in susceptible persons. Based on available data, the classification criteria are not met.			
Ingestion	Based on available data, the classification criteria are not met.			
Symptoms related to the physical	, chemical and toxicological characteristics			
Symptoms	Prolonged contact may cause redness and irritation.			
Numerical measures of toxicity				

Acute toxicity The following values are calculated based on chapter 3.1 of the GHS document ATEmix (dermal) 4,055.20 mg/kg ATEmix (inhalation-vapour) 534.81 mg/l

.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3360 µL/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
2768-02-7	(Rattus) OECD 401	cuniculus)	OECD TG 403
1-Propanamine,	LD50 (Rattus) > 2000 mg/ kg	LD50 (Oryctolagus cuniculus)	
3-(trimethoxysilyl)-	(2,97 ml/kg) (OECD 401)	> 2000 mg/kg 11,3 ml/kg)	
13822-56-5		OECD 402	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Serious eye damage/eye irritation No classification

No classification is proposed, based on conclusive negative data. By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void).

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 437 Bovine Corneal Opacity and Permeability (BCOP) test		Corneal	Product 100 %		Product score <3 Non-irritant

Respiratory or skin sensitisation

tion OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Product Information					
Method	Species	Exposure route	Results		
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses		
Sensitisation			were observed		

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.
STOT - single exposure	Based on available data, the classification criteria are not met.
STOT - repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
11.2. Information on other haz	ards
11.2.1. Endocrine disrupting prop	perties
Endocrine disrupting properties	No information available.
11.2.2. Other information	

Other adverse effects

No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202		

12.2. Persistence and degradability

Persistence and degradability No i

No information available.

Component Information TrimethoxyvinyIsilane (2768-02-7)					
Method	Method Exposure time Value Results				
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days		51 % Not readily biodegradable		

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Revision date 17-Mar-2021 Revision Number 2

Method	Exposure time	Value	Results
OECD Test No. 301A: Ready	28 days		Not readily biodegradable 67
Biodegradability: DOC Die-Away			%
Test (TG 301 A)			

12.3. Bioaccumulative potential

Bioaccumulation

There is no data for this product.

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane	1.1	-
2768-02-7		

12.4. Mobility in soil

Mobility in soil

No information available.

.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	The substance is not PBT / vPvB

12.6. Other adverse effects

Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products	Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
Contaminated packaging	Handle contaminated packages in the same way as the product itself.
European Waste Catalogue	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
Other information	Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Revision date 17-Mar-2021 Revision Number 2

IMDG		
14.1 UN number or ID number	Not regulated	
14.2 Proper Shipping Name	Not regulated	
14.3 Transport hazard class(es)	Not regulated	
14.4 Packing group	Not regulated	
14.5 Marine pollutant	NP	
14.6 Special Provisions	None	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable		
Air transport (ICAO-TI / IATA-DGR		
14.1 UN number or ID number	Not regulated	

Not regulated
Not regulated
Not regulated
Not regulated
Not applicable
None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009 Not applicable

Persistent Organic Pollutants Not applicable

National regulations

France

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

Germany____

Ordinance on Industrial Safety and Health - Germany - BetrSichV No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands) Not Listed

DenmarkRegistration number(s) (P-no.)No information availableNorwayRegistration number(s) (PRN-no.)No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H332 Harmful if inhaled

Legend

TWĂ	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue

Key literature references and sources for data No information available

Prepared By	Product Safety & Regulatory Affairs
Revision date	17-Mar-2021
Indication of changes	
Revision note	Not applicable.
Training Advice	No information available
Further information	No information available

BOSTIK H750 SEALNBOND PREMIUM BLACK

Supercedes Date: 17-Mar-2021

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet