

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
Supersedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product Identifier

**Product Name** BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
**Pure substance/mixture** Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Recommended use** Sealant.  
**Uses advised against** Not to be used in production of toys or childcare articles. Consumer use.

### 1.3. Details of the supplier of the safety data sheet

**Company Name**  
Bostik SA  
420 rue d'Estienne d'Orves  
92700 Colombes  
FRANCE  
Tel: +33 (0)1 49 00 90 00

**E-mail address** SDS.box-EU@bostik.com

### 1.4. Emergency telephone number

**Emergency Telephone** No information available

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Not classified

### 2.2. Label Elements

Not classified

**Signal word**  
None

**Hazard statements**  
Not classified

#### EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction  
EUH208 - Contains Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate. May produce an allergic reaction  
EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust  
EUH210 - Safety data sheet available on request

**Special provisions concerning the labelling of certain mixtures**  
Reserved for industrial and professional use.

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
Supersedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

## 2.3. Other Hazards

No information available

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
3-butyl-1-[4-({4-[(butylcarbamoyl)amino]phenyl}methyl)phenyl]urea	416-600-4	--	1 - <5	Aquatic Chronic 4 (H413)		01-0000016345-72-xxxx
Titanium dioxide	236-675-5	13463-67-7	1 - <5	Carc. 2 (H351i)		01-2119489379-17-XXXX
N,N-dibenzylidene polyoxypropylene diamine (polymer)	-	136855-71-5	1 - <2.5	Skin Irrit. 2 (H315)		[7]
C.I. Pigment Black 26	269-056-3	68186-94-7	0.1 - <1	-		01-2119457599-19-XXXX
Aromatic Polyisocyanate	-	53317-61-6	0.1 - <1	Eye Irrit. 2 (H319) Skin Sens. 1 (H317)		[7]
Ethyl acetate	205-500-4	141-78-6	0.1 - <1	Eye Irrit. 2 (H319) STOT SE 3 (H336) Flam. Liq. 2 (H225) (EUH066)		01-2119475103-46-XXXX
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	915-687-0	1065336-91-5	0.01 - <0.1	Skin Sens. 1A (H317) Aquatic Acute 1 (H400) Aquatic Chronic 1 (H410)		01-2119491304-40-XXXX
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane	924-669-1	192526-20-8	0.01 - <0.1	Skin Sens. 1A (H317)		01-2120768758-32-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

# SAFETY DATA SHEET

BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
Supercedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	If medical advice is needed, have product container or label at hand. Show this safety data sheet to the doctor in attendance.
<b>Inhalation</b>	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a doctor.
<b>Skin contact</b>	Wash skin with soap and water. In the case of skin irritation or allergic reactions see a doctor.
<b>Ingestion</b>	Clean mouth with water. Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person.

### 4.2. Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	Prolonged contact may cause redness and irritation.
-----------------	---

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Note to doctors</b>	Treat symptomatically.
------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
<b>Unsuitable extinguishing media</b>	Full water jet. Do not scatter spilled material with high pressure water streams.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards arising from the chemical</b>	Thermal decomposition can lead to release of toxic and corrosive gases/vapours.
<b>Hazardous combustion products</b>	Carbon oxides. Carbon dioxide (CO <sub>2</sub> ). Nitrogen oxides (NO <sub>x</sub> ). Hydrochloric acid. Sulphur oxides.

### 5.3. Advice for firefighters

<b>Special protective equipment for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.
---	--

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Ensure adequate ventilation. Avoid contact with skin, eyes or clothing.
<b>Other information</b>	Ventilate the area. Prevent further leakage or spillage if safe to do so.

# SAFETY DATA SHEET

BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
Supercedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

**For emergency responders** Use personal protection recommended in Section 8.

## 6.2. Environmental precautions

**Environmental precautions** Do not flush into surface water or sanitary sewer system. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

## 6.3. Methods and material for containment and cleaning up

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

## 6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

## **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

**General hygiene considerations** Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Take off all contaminated clothing and wash it before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feedingstuffs.

### 7.3. Specific end use(s)

**Specific Use(s)**  
Sealant.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

#### Exposure Limits

**Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.**

**Derived No Effect Level (DNEL)** No information available

Derived No Effect Level (DNEL)			
3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

Long term Systemic health effects	Inhalation	49.37 mg/m <sup>3</sup>	
Long term Systemic health effects	Dermal	140 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>Ethyl acetate (141-78-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	63 mg/kg bw/d	
worker Short term Systemic health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
worker Short term Local health effects	Inhalation	1468 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	

<b>Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate (1065336-91-5)</b>			
<b>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1.7 mg/m <sup>3</sup>	
worker Long term Systemic health effects	Dermal	4.7 mg/kg bw/d	

<b>Derived No Effect Level (DNEL)</b>			
<b>3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Long term Systemic health effects	Inhalation	7.4 mg/m <sup>3</sup>	
Long term Systemic health effects	Dermal	50 mg/kg bw/d	
Long term Systemic health effects	Oral	5 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term	Oral	700 mg/kg bw/d	

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

Systemic health effects			
-------------------------	--	--	--

<b>Ethyl acetate (141-78-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	4.5 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	37 mg/kg bw/d	
Consumer Short term Systemic health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Local health effects	Inhalation	367 mg/m <sup>3</sup>	
Consumer Short term Local health effects	Inhalation	734 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Inhalation	367 mg/m <sup>3</sup>	

<b>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	0.3 mg/m <sup>3</sup>	
Consumer Long term Systemic health effects	Dermal	1.7 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.2 mg/kg bw/d	

**Predicted No Effect Concentration (PNEC)** No information available.

<b>Predicted No Effect Concentration (PNEC)</b>	
<b>3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Sewage treatment plant	10 mg/l
Freshwater sediment	76.36 mg/kg dry weight
Marine sediment	7.636 mg/kg dry weight
Soil	15.15 mg/kg dry weight

<b>Titanium dioxide (13463-67-7)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
Supersedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

<b>Ethyl acetate (141-78-6)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.26 mg/l
Marine water	0.026 mg/l
Freshwater sediment	1.25 mg/kg
Marine sediment	0.125 mg/kg
Soil	0.24 mg/kg
Microorganisms in sewage treatment	650 mg/l

<b>Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)</b>	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.1 mg/l
Marine water	0.01 mg/l
Sewage treatment plant	100 mg/l
Freshwater sediment	0.428 mg/kg dry weight
Marine sediment	0.043 mg/kg dry weight

## 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas.

### Personal Protective Equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

**Hand protection** Nitrile rubber. Butyl rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374

**Skin and body protection** Suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Recommended filter type:** Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases and vapours filter conforming to EN 14387.

**Environmental exposure controls** Prevent product from entering drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**Physical state** Solid  
**Appearance** Paste  
**Colour** Dark Grey  
**Odour** Characteristic  
**Odour threshold** No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	No data available	
Flash point	> 100 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapour pressure	No data available	
Relative vapour density	No data available	
Relative density	No data available	
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	

# SAFETY DATA SHEET

BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
Supersedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	600 Pa.s	@ 20 °C
Explosive properties	No data available	
Oxidising properties	No data available	

## 9.2. Other information

Solid content (%)	No information available	
VOC Content (%)	1.6 g/L / 0.12 %	European directive n°2010/75/UE
Density	1.31	

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Reactivity No information available.

### 10.2. Chemical stability

Stability Stable under normal conditions.

#### Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

### 10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

### 10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

### 10.5. Incompatible materials

Incompatible materials None known based on information supplied.

### 10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

### 11.1. Information on toxicological effects

#### Information on likely routes of exposure

##### Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.



# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

**Ingestion** Based on available data, the classification criteria are not met.

## Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Prolonged contact may cause redness and irritation.

## Numerical measures of toxicity

### Acute toxicity

### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
3-butyl-1-[4-((butylcarbamoyl)amino)phenyl] methyl)phenyl]urea --	>2000 mg/Kg (Rattus) (OECD 401)	>2000 mg/Kg (Rattus) (OECD 402)	
Titanium dioxide 13463-67-7	>10000 mg/kg (Rattus)	LD50 > 10000 mg/Kg	>5 mg/l
C.I. Pigment Black 26 68186-94-7	>10000 mg/kg Rat		
Aromatic Polyisocyanate 53317-61-6	LD50 >2000 mg/Kg (Rattus)		LC50 >3.820 mg/L (Rattus) 4h dust/mist
Ethyl acetate 141-78-6	=5620 mg/kg (Rattus)	> 18000 mg/kg (Oryctolagus cuniculus) > 20 mL/kg (Oryctolagus cuniculus)	LC0 29.3 mg/l air
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-pi peridyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperi dyl sebacate 1065336-91-5	LD50 = 3230 mg/Kg (Rat)	LD50 >3170 mg/Kg (Rat)	
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilan e 192526-20-8	>2000 mg/Kg (Rattus) (OECD 423)	>2000 mg/Kg (Rattus) (OECD 402)	

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. May cause skin irritation.

Component Information					
Titanium dioxide (13463-67-7)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion					Non-irritant

**Serious eye damage/eye irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

**Carcinogenicity** Based on available data, the classification criteria are not met.

Chemical name	European Union
Titanium dioxide 13463-67-7	Carc. 2

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component Information		
Titanium dioxide (13463-67-7)		
Method	Species	Results
Oral	Rat	Not Carcinogenic

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
3-butyl-1-[4-({4-[(butylcarbamoyl)amino]phenyl}methyl)phenyl]urea --	-	LC50 (96h) >120 mg/L Danio rerio (OECD 203)	-	EC50 (48h) >100 mg/L Daphnia magna (OECD 202)		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
C.I. Pigment Black 26 68186-94-7	-	96H >100000 mg/l	-	-		
Ethyl acetate 141-78-6	EC50: =3300mg/L (48h, Desmodesmus subspicatus)	LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss) LC50: 220 - 250mg/L (96h, Pimephales	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50: =560mg/L (48h, Daphnia magna)		

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	-	promelas) LC50 (96h) =0.9 mg/L	-	-		
Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane 192526-20-8	EC50 (72h) >100 mg/L Algae (Raphidocelis subcapitata) (OECD 201)	LC50 (96h)>100 mg/L Fish (Brachydanio rerio) (OECD 203)	-	EC50 (48h) >100 mg/L Daphnia magna (OECD 202)		

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Component Information			
3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea (--)			
Method	Exposure time	Value	Results
OECD Guideline 310	28 days	0.4%	Not readily biodegradable
OECD Test No. 301B: Ready Biodegradability: CO2 Evolution Test (TG 301 B)	28 days	11%	Not readily biodegradable

Aromatic Polyisocyanate (53317-61-6)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)		biodegradation	34 % Not readily biodegradable

Reaction product of Hexamethylene diisocyanate, oligomers with Mercaptopropyltrimethoxysilane (192526-20-8)			
Method	Exposure time	Value	Results
OECD Test No. 301C: Ready Biodegradability: Modified MITI Test (I) (TG 301 C)	28 days	3.85%	Not readily biodegradable

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

### Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
3-butyl-1-[4-({ 4-[(butylcarbamoyl)amino]phenyl} methyl)phenyl]urea --	5.5	-
Ethyl acetate 141-78-6	0.6	30

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

# SAFETY DATA SHEET

BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
Supercedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

**PBT and vPvB assessment** The product does not contain any substance(s) classified as PBT or vPvB. .

Chemical name	PBT and vPvB assessment
Titanium dioxide 13463-67-7	The substance is not PBT / vPvB PBT assessment does not apply
C.I. Pigment Black 26 68186-94-7	The substance is not PBT / vPvB PBT assessment does not apply
Ethyl acetate 141-78-6	The substance is not PBT / vPvB PBT assessment does not apply
Reaction mass of Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and Methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate 1065336-91-5	The substance is not PBT / vPvB

## 12.6. Other adverse effects

**Other adverse effects** No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Do not reuse empty containers. Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated

# SAFETY DATA SHEET

BOSTIK P795 SEAL'N'FLEX PREMIUM GREY  
Supercedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

14.4 Packing group Not regulated  
14.5 Environmental hazards Not applicable  
14.6 Special Provisions None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### **EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction**

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH Annex XVII
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1	52[b].
Diisononyl phthalate	28553-12-0	52[a].

#### **52**

Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children

##### **Substance subject to authorisation per REACH Annex XIV**

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

##### **Ozone-depleting substances (ODS) regulation (EC) 1005/2009**

Not applicable

##### **Persistent Organic Pollutants**

Not applicable

#### National regulations

##### France

Chemical name	French RG number
Ethyl acetate 141-78-6	RG 84

##### Germany

##### **Ordinance on Industrial Safety and Health - Germany - BetrSichV**

No flammable liquids in accordance with BetrSichV

**Water hazard class (WGK)** slightly hazardous to water (WGK 1)

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
Supersedes Date: 05-Oct-2020

Revision date 28-Jan-2021  
Revision Number 1.01

**TRGS - 510 Storage Class** Storage Class 11 : Combustible solids

## Netherlands

**List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)**

Not Listed

## Denmark

## Norway

## 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

## **SECTION 16: Other information**

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H410 - Very toxic to aquatic life with long lasting effects

H413 - May cause long lasting harmful effects to aquatic life

#### **Legend**

TWA

TWA (time-weighted average)

STEL

STEL (Short Term Exposure Limit)

Ceiling

Ceiling Limit Value

\*

Skin designation

SVHC

Substance(s) of Very High Concern

PBT

Persistent, Bioaccumulative, and Toxic (PBT) Chemicals

vPvB

Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE

Specific target organ toxicity - Repeated exposure

STOT SE

Specific target organ toxicity - Single exposure

EWC

European Waste Catalogue

#### **Key literature references and sources for data**

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 28-Jan-2021

#### Indication of changes

**Revision note** SDS sections updated: 3.

**Training Advice** No information available

**Further information** No information available

**This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006**

#### **Disclaimer**

# SAFETY DATA SHEET

**BOSTIK P795 SEAL'N'FLEX PREMIUM GREY**  
**Supersedes Date:** 05-Oct-2020

**Revision date** 28-Jan-2021  
**Revision Number** 1.01

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**