

This safety data sheet was created pursuant to the requirements of:
Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008
This SDS is for generic information purposes and does not reflect required country specific information for OEL

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020

Revision date 13-Nov-2020 Revision Number 2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product Identifier

Product Name FOLIEFIX SPUR LM Q603F1491 (GREEN)

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants.

Uses advised againstNot to be used in production of toys or childcare articles.

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Benelux B.V. Denariusstraat 11 4903 RC Oosterhout The Netherlands

Tel: + 31 162 491 000

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Emergency Telephone No information available

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Serious eye damage/eye irritation Category 2 - (H319)

2.2. Label Elements



Signal word Warning

Hazard statements

H319 - Causes serious eye irritation.

Precautionary statements

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P264 - Wash face, hands and any exposed skin thoroughly after handling.

Europe - BE Page 1/13

Revision date 13-Nov-2020

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

P280 - Wear eye protection/ face protection.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical advice/attention.

2.3. Other Hazards

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Trimethoxyvinylsilane	220-449-8	2768-02-7	1 - <2.5	Acute Tox. 4 (H332) Flam. Liq. 3 (H226)		01-2119513215- 52-XXXX
1-Propanamine, 3-(trimethoxysilyl)-	237-511-5	13822-56-5	1 - <2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318)		01-2119510159- 45-XXXX
Chromium oxide (Cr2O3)	215-160-9	1308-38-9	0.1- <1	-		01-2119433951- 39-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand. Show this safety

data sheet to the doctor in attendance.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contactWash skin with soap and water. In the case of skin irritation or allergic reactions see a

Europe - BE Page 2/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 **Revision Number** 2

doctor.

Ingestion Call a doctor immediately. If swallowed, rinse mouth with water (only if the person is

conscious). Small amounts of toxic methanol are released by hydrolysis.

Revision date 13-Nov-2020

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products

Carbon dioxide (CO2). Silicon dioxide.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Do not get Personal precautions

in eyes, on skin, or on clothing.

Other information Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section **Environmental precautions**

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containment Use a non-combustible material like vermiculite, sand or earth to soak up the product

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

Europe - BE Page 3 / 13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

Revision date 13-Nov-2020

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Keep at temperatures between 5 and 35 °C. Keep away from food, drink and animal

feedingstuffs. Protect from moisture.

7.3. Specific end use(s)

Specific Use(s)

Adhesives and/or sealants.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Methyl alcohol	TWA: 200 ppm
67-56-1	TWA: 260 mg/m³ *
Chromium oxide (Cr2O3) 1308-38-9	TWA: 2 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)							
Trimethoxyvinylsilane (2768-0	Trimethoxyvinylsilane (2768-02-7)						
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor				
worker Systemic health effects Long term	Inhalation	27,6 mg/m³					
worker Systemic health effects Long term	Dermal	3,9 mg/kg bw/d					

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)							
Туре	1	Derived No Effect Level (DNEL)	Safety factor				
worker	Inhalation	58 mg/m³					

Europe - BE Page 4/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Revision date 13-Nov-2020 Supercedes Date: 09-Nov-2020 **Revision Number** 2

Long term Systemic health effects			
worker Long term	Dermal	8.3 mg/kg bw/d	
Short term worker	Inhalation	58 mg/m³	
Short term worker	Dermal	8.3 mg/kg bw/d	

Derived No Effect Level (DNEL)								
Trimethoxyvinylsilane (2768-0	Trimethoxyvinylsilane (2768-02-7)							
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor					
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m³						
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d						
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d						

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)					
Trimethoxyvinylsilane (2768-02-7)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.34 mg/l				
Marine water	0.034 mg/l				
Microorganisms in sewage treatment	110 mg/l				

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)					
Environmental compartment	Predicted No Effect Concentration (PNEC)				
Freshwater	0.33 mg/l				
Microorganisms in sewage treatment	13 mg/l				
Soil	0.04 mg/l				
Marine water	0.033 mg/l				

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Wear safety glasses with side shields (or goggles). Eye protection must conform to Eye/face protection

standard EN 166

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection None under normal use conditions.

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

Europe - BE Page 5/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

Revision date 13-Nov-2020

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid Appearance Paste

Colour See section 1 for more information

Odour Characteristic

Odour threshold No information available

Property Values Remarks • Method

pH Not applicable .

Melting point / freezing point No data available

Boiling point / boiling range No data available °C

Flash point > 100 °C
Evaporation rate No data available
Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressureNo data availableRelative vapour densityNo data availableRelative densityNo data available

Water solubility Product cures with moisture

Solubility(ies) No data available Partition coefficient No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity > 21 mm²/s **Dynamic viscosity** No data available **Explosive properties** No data available Oxidising properties No data available

9.2. Other information

Solid content (%)No information availableVOC Content (%)30.2 g/L / 2.48 %Density1.22 g/cm³

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Europe - BE Page 6/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)
Supercedes Date: 09-Nov-2020

Conditions to avoid Protect from moisture. Product cures with moisture.

10.5. Incompatible materials

Incompatible materials None known based on information supplied.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Small amounts of methanol (CAS 67-56-1) are

Revision date 13-Nov-2020

Revision Number 2

formed by hydrolysis and released upon curing.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause irritation. Prolonged contact may cause redness and irritation. Specific test

data for the substance or mixture is not available. Causes mild skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May cause redness and tearing of the eyes. Prolonged contact may cause redness and

irritation.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 20,979.60 mg/kg
ATEmix (inhalation-vapour) 856.76 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg	= 3360 μL/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
2768-02-7	(Rattus) OECD 401	cuniculus)	OECD TG 403
1-Propanamine,	LD50 (Rattus) > 2000 mg/ kg	LD50 (Oryctolagus cuniculus)	
3-(trimethoxysilyl)-	(2,97 ml/kg) (OECD 401)	> 2000 mg/kg 11,3 ml/kg)	
13822-56-5		OECD 402	
Chromium oxide (Cr2O3)	LD50 > 5000 mg/kg		
1308-38-9	(Rattus) OECD 401		

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. May cause skin irritation.

Europe - BE Page 7/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Revision date 13-Nov-2020 Supercedes Date: 09-Nov-2020 **Revision Number** 2

Component Information							
Trimethoxyvinylsilane (2768-02-7)							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant		

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Component Information							
Trimethoxyvinylsilane (2768-02-7)							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
OECD Test No. 405:	Rabbit	eye		24 hours	Non-irritant		
Acute Eye							
Irritation/Corrosion							

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)							
Method Species Exposure route Effective dose Exposure time Results							
OECD Test No. 405:	Rabbit	eye		72 hours	irritant		
Acute Eye							
Irritation/Corrosion							

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser

1-Propanamine, 3-(trimethoxysilyl)-	(13822-56-5)		
Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Did not cause sensitisation
Sensitisation			on laboratory animals

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 471: Bacterial Reverse	in vitro	Not mutagenic
Mutation Test		-

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Component Information		
Trimethoxyvinylsilane (2768-02-7)		
Method	Species	Results
OECD Test No. 422: Combined Repeated	Rat	Not Classifiable
Dose Toxicity Study with the		
Reproduction/Developmental Toxicity		
Screening Test		

1-Propagamine	3-(trimethoxysilyl)-	(13822-56-5)
H-I TODAHAHIIIG.	3-(ti ii i i G ti i O	110022-00-01

Europe - BE Page 8/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Revision date 13-Nov-2020 Supercedes Date: 09-Nov-2020 **Revision Number** 2

Method	Species	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Not Classifiable

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Component Information					
Trimethoxyvinylsilane (27	68-02-7)				
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation					
Toxicity: 90-day Study					

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202		
Chromium oxide (Cr2O3) 1308-38-9	- ′	LC50: >10000mg/L (96h, Danio rerio)	-	-		

12.2. Persistence and degradability

No information available. Persistence and degradability

Component Information			
Trimethoxyvinylsilane (2768-02-7)			
Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily
Biodegradability: Manometric	_		biodegradable
Respirometry Test (TG 301 F)			

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)			
Method	Exposure time	Value	Results
OECD Test No. 301A: Ready	28 days		Not readily biodegradable 67
Biodegradability: DOC Die-Away	-		%

Europe - BE Page 9/13

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 **Revision Number** 2

Revision date 13-Nov-2020

Test (TG 301 A)

12.3. Bioaccumulative potential

There is no data for this product. Bioaccumulation

Component Information

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Trimethoxyvinylsilane	1.1	-
2768-02-7		

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane 2768-02-7	The substance is not PBT / vPvB
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	The substance is not PBT / vPvB
Chromium oxide (Cr2O3)	The substance is not PBT / vPvB
1308-38-9	PBT assessment does not apply

12.6. Other adverse effects

No information available. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Uncured product should be disposed of as hazardous waste. Dispose of contents/container in accordance with local, regional, national, and international

regulations as applicable.

Handle contaminated packages in the same way as the product itself. Contaminated packaging

according to EWC / AVV

Waste codes / waste designations 15 01 10*: Packaging containing residues of or contaminated by dangerous substances. 16 03 03* inorganic wastes containing hazardous substances. 16 05 05 gases in pressure containers other than those mentioned in 16 05 04. Waste codes should be assigned by the user based on the application for which the product was used.

08 04 09* waste adhesives and sealants containing organic solvents or other dangerous

European Waste Catalogue

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

Europe - BE Page 10/13

Revision date 13-Nov-2020

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

IMDG

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group

Not regulated
Not regulated
Not regulated
Not regulated

14.5 Marine pollutant NP
14.6 Special Provisions None

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH
		Annex XVII
Diisononyl phthalate	28553-12-0	52[a].

52

Not to be used in toys or childcare articles above 0.1% which can be placed in the mouth by children

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Europe - BE Page 11/13

Revision date 13-Nov-2020

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Chemical name	French RG number	
Chromium oxide (Cr2O3)	RG 10	
1308-38-9		

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) slightly hazardous to water (WGK 1)

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Denmark

Norway

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H315 - Causes skin irritation

H318 - Causes serious eye damage

H332 - Harmful if inhaled

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

Europe - BE Page 12/13

Revision date 13-Nov-2020

FOLIEFIX SPUR LM Q603F1491 (GREEN)

Supercedes Date: 09-Nov-2020 Revision Number 2

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Nov-2020

Indication of changes

Revision note Not applicable.

Training Advice When working with hazardous materials, regular training of operators is required by law

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Europe - BE Page 13/13